TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7358)

Set a cedar post 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on North face; from which
A fir, 18" dia., bears N.58°E., 29 lks., mkd: ¼ S BT.
A cedar, 15" dia., bears S.42°W., 9 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Ray Tracy - Mike Stone - Sept. 1965 - C.S. File 53/67-12

Found - Orig. 15" now 24" cedar S.42°W., 5.9 ft. shows good scribing "¼S" on old face.
20" Fir down & rotted checks bearing & dist. for orig. NE BT.
Set brass cap at cor. mkd: COUNTY SURVEYORS T30S R8W ¼ S 20
OFFICE 1965 S 29
New BTs- 12" cedar bears N.4°E., 12.6 ft scribed ¼ S20 CS BT.
7" D.Fir bears S.12°W., 15.0 ft scribed ¼ S29 CS BT.
Note - Boulder Creek 45 ft. north of ¼ corner.