

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5, T31-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7309)

-
- Marked a Laurel 14" dia., for the cor. to secs. 4, 5, 32 and 33, mkd. T30S R8W S33 on the NE. face, T31S S4 on the SE. face; S5 on the SW. face, and S32 on the NW. face. Also 4 notches on the E. and 2 notches on the W. side, from which
- A Laurel 12" dia., bears N.50°E., 49 lks. dist. mkd. T30S R8W S33 BT.
 - A Laurel 16" dia., bears S.70°E., 34 lks. dist. mkd. T31S R8W S4 BT.
 - A Sugar Pine 10" dia., bears S.41°W., 9 lks. dist., mkd. T31S R8W S5 BT.
 - A Laurel 5" dia., bears N.18°W., 27 lks. dist. mkd. T30S R8W S32 BT.

BLM Resurvey by C. Albert White, Harold D. Corbing Cadastral Surveyor and Donald R. Beck, Surveying Technician, Under Group #446, Surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 31 Page(s) 13192)

-
- The Sec. Cor., monumented by the rotted shell of the original Madrone corner tree, 18" dia., with old axe marks and blazes visible, from which the original bearing trees:
- A Madrone 15" dia., bears N.56°E., 49 lks. dist., with healed blaze. (Rec. brg. N.50°E.)
 - A Madrone 25" dia., bears S.70°E., 34 lks. dist., with opened and rotted blaze.
 - A Sugar Pine 12" dia., bears S.41°W., 9 lks. dist., with scribe marks T31S R8W visible on partially opened blaze.
 - A down Madrone 8" dia., bears N.18°W., 27 lks. dist., with rotted blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 21" in the ground, with brass cap mkd:

T 30 S R 8 W
 S 32 | S 33
 S 5 | S 4
 T 31 S
 1961

- from which new bearing trees:
- A Fir 10" dia., bears N.13°E., 60 lks. dist. mkd. T30S R8W S33 BT.
 - A Cedar 12" dia., bears S.37½°E., 73 lks. dist. mkd. T31S R8W S4 BT.
 - A Cedar 8" dia., bears S.77°W., 56 lks. dist. mkd. T31S R8W S5 BT.

(Cont. Next Page)

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5, T31-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Sugar Pine 60" dia., bears N.42°W., 40 lks. dist. mkd.
T30S R8W S32 BT.

Gerald Nygren - For: Seneca Jones Timber - 4/2015 - M169-26

Found - 1961 BLM brass cap
1882: 10" S.Pine, now snag, bears N.41°W., visible
scribe.
1961: 18" Cedar bears S.37°30'E., 48.2' visible
scribe.
12" cedar bears S.77°W., 37.0'
60" S.Pine, now stump, bears N.42°W., 26.4',
visible scribe.
New - 16" cedar bears N.27°E., 24.1', scribed: "T30S R8W
S33 BT"
9" D.Fir bears N.45°W., 60.2', scribed: "T30S R8W
S32 BT"

BLM dependent resurvey by Jeffrey O. Covington, Cadastral
Surveyor, under Group No. 2972, surveyed May 2020/Feb2021 -
(DCSO records Vol. 59 Page(s) 23949)

The cor. of secs. 4, 5, 32, and 33, reported by White and
Corbin in 1960-62; perpetuated by Nygren, in 2015; monumented
with an iron post, 2½" dia., firmly set, projecting 12" above
ground, in a mound of stone, 2 ft. base, 8" high, with a
brass cap (properly) mkd.

from which the remains of the BTs reported by White & Corbin
A cedar, 18" dia., bears S.37½°E., 48.2 ft., with a healed
blaze.

A sugar pine snag, 10" dia., bears S.34°W., 8.5 ft., with
scribe marks T31 S R8W S5 B visible on open blaze.
(Original Record, S. 41° W., 5.9 ft.)

A cedar, 12" dia., bears S.77°W., 37.0 ft., with a healed
blaze.

A decayed sugar pine stump, 60" dia., bears N.42°W., 26.4
ft., with scribe marks T30S R8W S32 BT visible on open
blaze.

and the bearing trees mkd. by Nygren

A cedar, 17" dia., bears N.24¾°E., 28.8 ft., with scribe
marks T30S R8W S33 BT visible on partially healed
blaze.

A fir, 11" dia., bears N.46¼°W., 59.9 ft., with scribe
marks T30S R8W S32 BT visible on partially healed
blaze.

continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5, T31-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Daniel A Renton, Minister-Glaeser Surveying - Garrett Finch & Crew - For: US Department of Interior, BLM - Snake Eyes - Task H - June 6, 2023 - M178-75 A-E

-
- Found - A 3¼" BLM brass cap (properly mkd) in mound of stone 1.3 ft above ground from which:
- A 10" snag bears S.34°W., 8.5 ft with BT sign and scribing "T31S R8W S5 B" (1882)
 - A 13" cedar bears S.77°W., 37.2 ft with healed blaze, BT sign and side nail (1961)
 - An 11" Fir bears N.46¼°W., 59.9 ft with healed blaze, BT sign and side nail (2015)
 - A 52" stump (5 ft high) bears N.42°W., 26.4 ft with BT sign and scribing "T30S R8W S32 BT" (1961)
 - A 17" Cedar bears N.24¾°E., 23.8 ft with BT sign and scribing "T30S R8W S33 BT" (2015)
 - A 17" Cedar bears S.37½°E., 48.2 ft with healed blaze and BT sign (1961)
 - A 17" Madrone bears N.50°E., 29.7 ft with healed blaze and BT sign (1882)
 - A 17" Madrone bears S.70°E., 22.4 ft with rotted blaze and BT sign (1882)
 - A 14" stump (2 ft high) decayed bears N.13°E., 40.2 ft (1961)

Set chaining nail at side center, BT signs on front and rear, and painted red band for existing BTs