



TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor Secs 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original BTs  
A madrone, 20" dia., bears N.13°E., 15 lks., no marks visible on opened and decayed blaze. (Record, N.16°E.)  
A chinquapin snag, 8" dia., bears N.51½°W., 31 lks., no marks visible on opened and decayed blaze. (Rec N.50°W) and bearing trees mkd, by White and Beck. in 1963-64  
A fir, 18" dia., bears N.3½°E., 68 lks. with healed blaze.  
A fir, 9" dia., bears S.68°E., 40 lks., with healed blaze.  
A fir, 14" dia., bears S.32½°W., 44 lks. with healed blaze  
A fir, 9" dia., bears N.35°W., 12 lks., with healed blaze. (Record, N.32½°W.)

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2972, surveyed May 2020/Feb2021 - (DCSO records Vol. 59 Page(s) 23959-60)

-----  
The cor. of secs. 28, 29, 32, and 33, reported by Popken and Carlson in 1975, monumented with an iron post, 2½" dia., firmly set, projecting 10" above ground, with a brass cap (properly) mkd.  
from which the bearing trees reported by Popken and Carlson  
A fir, 32" dia., bears N.3½°E., 44.9 ft., with a healed blaze.  
A madrone, 24" dia., bears N.13°E., 9.9 ft., with axe marks visible on decayed open blaze. (Original)  
A fir, 23" dia., bears S.68°E., 26.4 ft., with a healed blaze.  
A fir, 30" dia., bears S.32½°W., 30.2 ft., with a healed blaze. (Record, 29.0 ft.)  
A fir, 24" dia., bears N.35°W., 7.9 ft., with a healed blaze.  
Corner is located E., 30 ft., of a creek, 1 ft. wide, course N.15°W.  
NAD 1983 (2011)  
Latitude: 42°55'30.16" N.      Longitude: 123°39'44.24" W.