TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7346)

Set a fir post 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on West face; from which
A chincapin, 5" dia., bears S.46°W., 40 lks., mkd: ¼ S BT.
A laurel, 8" dia., bears N.40°E., 8 lks., mkd: ¼ S BT.

BLM dependent resurvey by Donald R. Beck & C. Albert White, Cadastral Surveyor, under group #350 & 548, surveyed May 1963/July 1964 - (DCSO records Vol. 32 Page 13609)

The ¼ sec. cor. of secs. 28 & 29 determined at the record bearing & distance from the remains of the orig. BTs:
A madrone stump, decayed to a mulch bears N.40°E., 8 lks., no marks remain.
A chinquapin, 6" dia down & greatly decayed, bears S.46°W. 40 lks. mkd. with partial scribing, in reverse, on a fragment of overgrowth.
At the corner point
Set an iron post, 28 long, 2½" dia., 22" in the ground, with brass cap marked: ¼
S 29|S 28
T30S R8W
1963
from which new BTs
A fir, 11" dia., bears N.71°E., 9 lks., mkd: ¼ S28 BT.
A fir, 18" dia., bears S.71°W., 33 lks., mkd: ¼ S29 BT.

Douglas Co. Surveyors Office - Larry E. Monrean - P.L. Earle & J.H. Cook - 1/21/1976 - C.S. File 59/2-11

Found - A USBLM brass cap properly marked and set firmly in place.
A fir 12" dia., uprooted. Approx. standing position bears N 71°E.,5.9 ft. Partial scribe visible in blaze.
A fir 19" dia. uprooted. Approx. standing position bears S.71°W., 21.8 ft. Partial scribe visible in blaze.
New BTs- 7" dia. W.Fir bears S.62½°W., 14.4 ft. Tree blazed find scribe "¼ S29 CS BT"
12" dia. W.Fir bears N.26°E.,44.5 ft. Tree blazed and scribed "¼ S 28 CS BT"
Mag. Dec. 20°E.