

PRIMARY CORNER DESCRIPTION Cor Secs 20, 21, 28 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7346)  
 -----  
 Set a stone 20x16x6" in the ground for cor. of secs. 20, 21, 28, & 29 mkd with 2 notches on South & 4 notches on East edges, from which  
 A fir, 12" dia. bears N.80°E., 44 lks mkd: T30S R8W S21 BT  
 A fir, 14" dia. bears S.74°E., 35 lks mkd: T30S R8W S28 BT  
 A fir, 18" dia. bears S.58°W., 54 lks mkd: T30S R8W S29 BT  
 A Live Oak, 10" dia., bears N.86°W., 40 lks., mkd: T30S R8W S20 BT.

BLM dependent resurvey by Donald R. Beck & C. Albert White, Cadastral Surveyor, under group #350 & 548, surveyed May 1963/July 1964 - (DCSO records Vol. 32 Page(s) 13609-10)  
 -----  
 The cor. of secs. 20, 21, 28 and 29, monumented with an unmarked sandstone boulder, 16x8x6", lying loose on top of a sandstone boulder and outcropping, 6x6x4 ft., from which the original BTs:  
 A fir, 21" dia., bears N.80°E., 44 lks., mkd. with illegible bark scribing. Reblazed and marked T30S R8W S21 BT.  
 A fir, 18" dia., bears S.74°E., 35 lks., mkd. T30 R8W 28 B, on a good bark blaze.  
 A fir, 25" dia., bears S.58°W., 54 lks., mkd. T30 R8W 29, on a bark blaze. Reblazed and marked T30S R8W S29 BT.  
 A live oak, 9" dia., bears N.86°W., 40 lks., mkd. with a nearly healed blaze.  
 At the corner point  
 Set an iron pipe, 8" long, 1" dia., 7" in a drilled hole in the sandstone boulder and outcropping with a brass tablet, 3¼" dia., 3½" stem, driven into the iron pipe, with top marked  

T30S	R8W
S 20	S 21
S 29	S 28
1963	

 Deposit the orig. stone alongside the brass tablet.  
 No new BTs were mkd.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2972, surveyed May 2020/Feb2021 - (DCSO records Vol. 59 Page(s) 23961)  
 -----  
 The cor. of secs. 20, 21, 28, & 29, reported by Beck & White in 1963-64, monumented with an iron pipe, 1" dia., firmly set, with top flush with the surface of an exposed sandstone boulder, 4x6x4 ft. high, with a brass tablet, 3¼" dia., seated firmly in the iron pipe, with top (properly) mkd.  
 Continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original BTs reported by Beck and White

- A fir, 24" dia., bears N.80°E., 29.0 ft., with a healed blaze.
- A broken, hollowed fir snag, 19" dia., bears S.78°E., 23.1 ft., with a healed blaze. (Record, S.74°E.)
- A fir snag, 29" dia., bears S.66¼°W., 33.8 ft., with a healed blaze. (Record, S.58°W., 35.6 ft.)
- An oak, 14" dia., bears N.86°W., 26.4 ft., with a hollowed blaze.

and new bearing trees

- An oak, 11" dia., bears S.52½°E., 15.5 ft., mkd. T30S R8W S28 BT.
- An oak, 5" dia., bears S.58¼°W., 6.2 ft., mkd. X BT.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.