

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7348)  
-----  
Set an oak post 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on West face; from which  
    An Oak, 8" dia., bears S.80°W., 15 lks., mkd: ¼ S BT.  
    An Oak, 8" dia., bears S.54°E., 13 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John Powell & crew - 9/17/1969 - C.S. File 53/67-4  
-----  
Found - Orig. 8" now 12" Oak, alive, S.80°W., 9.7 ft. blaze open & axe marks, no scribe.  
          Orig. 8" now 16" Oak, down, S.54°E., 8.6 ft. open & scribe visible.  
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T30S R8W OFFICE 1969 ¼ S 20|S 21  
New BTs- 6" D.Fir S.72°E., 23.5 ft. mkd: "¼ S21 CS BT"  
          12" D.Fir S.50°W., 21.8 ft. mkd: "¼ S20 CS BT"  
This corner lies on moderate southerly slope, spring bears S.20°W., 62'.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2972, surveyed May 2020/Feb 2021 - (DCSO records Vol. 59 Page(s) 23961-2)  
-----  
The ¼ sec. cor. of secs. 20 and 21, perpetuated by Douglas County Surveyor's Office, on September 17, 1969; from original evidence no longer in existence; monumented with an iron post, 1¼" dia., firmly set, projecting 18" above ground, with a brass cap (properly) mkd.  
from which a BT mkd. by Douglas County Surveyor's Office  
    A fir, 22" dia., bears S.72½°E., 23.3 ft., with a healed blaze.  
and a new bearing tree  
    A pine, 8" dia., bears S.55°W., 21.7 ft., mkd. ¼ S20 BT.  
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.