

PRIMARY CORNER DESCRIPTION Cor Secs 16, 17, 20, & 21

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A fir, 15" dia., bears N.71°E., 21 lks., with fragmentary scribe marks visible on partially healed double blaze.
A W.Fir, 8" dia. bears S.81°E., 44½ lks., with scribe marks CS visible on partially healed double blaze.
A sugar pine, 23" dia., bears S.50°W., 20½ lks., with healed double blaze.
A fir, 7" dia., bears N.78°W., 12½ lks., with scribe marks S17 Cs BT visible on open blaze.

BLM dependent resurvey by Dale T. Bedell & Bryan S. Seibold, Cadastral Surveyors under Group No. 1494, surveyed July 1989/April 1993 - (DCS0 records Vol. 50 (Page(s) 19020-1)

The cor of secs. 16, 17, 20 and 21, monumented with an iron post, 1½" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd

from which the remaining original bearing tree
A madrone, 25" dia., bears N.14°E., 93 lks. no marks remaining on rotted blaze.
and the remains of the BTs mkd. by Tracy, in 1965

A root hole, bears N.71°E., 21 lks., with a down fir alongside, 11" dia., with scribe marks T30S R8W S16 C visible on partially healed blaze.

A fir stump, 6" dia., bears S.81°E., 44½ lks., with illegible scribe marks visible on partially healed blaze.

A pine snag, 23" dia., bears S.52½°W., 20½ lks. with healed blaze. (Record, S.50°W.)

A sawed fir stump, 8" dia., bears N.76°W., 12½ lks., with scribe marks CS BT visible on partially healed blaze. (Record, N.78°W.)

and new bearing trees

A fir, 7" dia. bears N.61½°E. 34 lks. mkd. T30S R8W S16 BT

A fir, 4" dia., bears S.78°E., 44 lks. mkd. X at breast height and BT at the base.

A cedar, 5" dia., bears N.21°W., 55 lks. mkd. X at breast height and BT at the base.

No suitable trees available in sec. 20.
The corner is located 55 lks. N. of a gravel road, 30 lks. wide, bearing N.85°E. and S.85°W.

DCS0-GIS Corner visitation - 4/24/2007 - Typed: 2/9/2011 - C.S. File 67/33-1

Monument - 2½" BC/IP
Comment - 2 live BTs

continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor Secs 16, 17, 20, & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2972, surveyed May 2020/Feb 2021 - (DCSO records Vol. 59 Page(s) 23962-3)

The cor. of secs. 16, 17, 20, and 21, reported by Bedell and Seibold in 1989-93, monumented with an iron post, 1¼" dia., firmly set, projecting 8" above ground, with a brass cap (properly) mkd.

from which the remains of the bearing trees reported by Bedell and Seibold

A madrone, 24" dia., bears N.14°E., 61.4 ft., no marks visible on a hollowed double blaze. (Original)

A fir snag, 11" dia., bears N.61½°E., 22.4 ft., with scribe marks T30S R8W S16 BT visible on partially healed blaze and healed upper blaze.

A roothole bears N.71°E., 13.9 ft., alongside of which is a fir wood fragment, with scribe marks 8W S16 CS and axe work.

A fir snag, 12" dia., bears S.78°E., 29.0 ft., with a healed double blaze.

A decayed pine snag, 15" dia., bears S.52½°W., 13.5 ft., with scribe marks T30S R8W S20 CS visible on open blaze.

A cedar, 14" dia., bears N.21°W., 35.2 ft., with a healed double blaze. (Record, 36.3 ft.)

and new bearing trees

A fir, 8" dia., bears S.66¾°E., 27.1 ft., mkd. T30S R8W S21 BT.

A cedar, 6" dia., bears S.42½°W., 15.9 ft., mkd. T30S R8W S20 BT.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.