

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor Secs 8, 9, 16, & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7349-50)

Set cedar post 4 ft. long, 4" sq., 24" in the ground for the corner to Secs. 8, 9, 16, & 17, marked T30S R8W S9 on the NE face, S16 on the SE face S17 on the SW face and S8 on the NW face. with 4 notches on the South and East edges, from which
A fir, 6" dia., bears N.65°E., 56 lks. mkd: T30S R8W S9 BT
A cedar, 14" dia., bears S.46°E., 27 lks., mkd: T30S R8W S16 BT.
A fir, 18" dia. bears S.15°W., 27 lks mkd: T30S R8W S17 BT
A fir, 20" dia., bears N.55°W., 49 lks mkd: T30S R8W S8 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby & Jack Barnett - March 24, 1965 - C.S. File 53/67-36

Found - Orig. 6" now 15" W.Fir N.55°E., (recorded N.65°E.) 37.0 ft. shows good scars.
Orig. 14" now 15" cedar snag S.46°E., 17.8 ft. shows scribe.
Orig. 18" now 24" D.Fir S.15°W., 17.8 ft. shows bark scribe.
Orig. 20" now 30" D.Fir N.55°W., 32.3 ft., shows scribe (bark)
Set brass cap at cor. mkd: COUNTY SURVEYORS T30S R8W S 8|S 9 OFFICE 1965 S17|S18
New BT - 8" W.Fir S.25°E., 34.7 ft. mkd: T30S R8W S16 CS BT.
rescribed -15" W.Fir N.55°E., 37.0 ft. mkd: T30S R8W S9 CS BT
24" D.Fir S.15°W. 17.8 ft. mkd: T30S R8W S17 CS BT
30" D.Fir N.55°W., 32.3 ft. mkd: T30S R8W S8 CS BT

7/1973 - FD 0k VRT, C.S. 56/34-17, straighten & reset brass cap

BLM dependent resurvey by Dale T. Bedell & Bryan S. Seibold, Cadastral Surveyors under Group No. 1494, surveyed July 1989/April 1993 - (DCSO records Vol. 50 (Page(s) 19022)

The cor. of secs. 8, 9, 16, and 17, perpetuated by Tracy, in 1965, monumented with an iron post, 1½" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd. from which the remains of the original BTs remarked by Tracy
A rotted fir stump, size indeterminate, bears N.55°E., 58 lks., with scribe marks T30S R8W S9 CS BT visible on open blaze. (Record, N.65°E., 56 lks.)
A cedar snag, 16 ins. diam., bears S.49½°E., 27 lks., with scribe marks T30S R8W S16 visible on open blaze. (Record, S.46°E.)
continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor Secs 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A root hole, bears S.15°W., 27 lks., with a down fir alongside, 24" dia., with illegible scribe marks visible on partially healed blaze.
A fir stump, 40" dia., bears N.55°W., 49 lks., with scribe marks 8 S visible on rotted blaze.
and a bearing tree mkd. by Tracy
A fir, 18" dia., bears S.25°E., 52 lks., with healed blaze and new bearing trees
A fir, 12" dia. bears N.35°E., 22 lks. mkd. T30S R8W S9 BT
A fir, 4" dia., bears S.67°W., 100 lks., mkd. X at breast height and BT and the base.
No suitable trees available in sec. 8.
Latitude 42°58'05.80"N Longitude 123°39'40.07"W (NAD 1927)
From this point, the BLM Geodetic Control Station EC41007, at latitude 42°58'03.492"N., longitude 123°39'36.870"W. (NAD 1927), determined by the NAVSTAR GPS, bears S.45°31'07"E., 5.053 chs., monumented with an aluminum cap, firmly set flush in concrete, with top mkd. EC41007 GPS 1989.

BLM resurvey by George M. Winter, Cadastral Surveyor, under Group No. 2698, surveyed April 2013/Feb. 2014 - (DCSO records Vol. 58 page(s) 23154)

The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 1½" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd.
from which the remains of the original bearing trees
A decayed stump, size indeterminate, bears N.55°E., 38.3 ft., with no marks visible.
A cedar snag, 16" dia., bears S.48¾°E., 19.2 ft., with fragmentary scribe marks visible on an open blaze. (Record, S.49½°E., 17.8 ft.)
A roothole bears S.15°W., 17.8 ft., with decayed stump laying alongside, 24" dia., with no marks visible.
A fir stump, 40" dia. bears N.55°W., 32.3 ft., with scribe marks 8W8S visible on a decayed blaze.
and remains of a bearing tree mkd. by the Douglas County Surveyor's Office in 1964-65
A fir, 24" dia., bears S.25°E., 34.3 ft., with a healed blaze.
and bearing trees mkd. by Bedell and Seibold in 1989-93
A fir, 18" dia., bears N.35°E., 14.5 ft., with a healed blaze.
A fir, 10" dia., bears S.67°W., 66.0 ft., with a healed double blaze.
continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor Secs 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a new bearing tree
A fir, 5" dia., bears N.47°W., 7.9 ft. mkd. T30S R8W S8 BT
From the corner
N., 75 ft., gravel road, 24 ft. wide, bears N.60°E. & S.60°W.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral
Surveyor, under Group No. 2972, surveyed May 2020/Feb 2021 -
(DCS0 records Vol. 59 Page(s) 23964-5)

The cor. of secs. 8, 9, 16, and 17, reported by Winter in
2013-14, monumented with an iron post, 1¼" dia., firmly set,
projecting 9" above ground, with a brass cap (properly) mkd.
from which the remains of the BTs reported by Winter
A fir, 19" dia., bears N.35°E., 14.5 ft., with a healed
blaze.
A decayed fir stump, size indeterminate, bears N.55°E.,
38.3 ft., no marks visible. (Original)
A cedar snag, 13" dia., bears S.48¼°E., 19.2 ft., with
illegible scribe marks visible on open blaze. (Orig.)
A fir, 29" dia., bears S.25°E., 34.3 ft., with a healed
blaze.
A roothole bears S.15°W., 17.8 ft., alongside of which is
an uprooted decayed fir stump, 24" dia., no marks
visible. (Original)
A fir, 16" dia., bears S.67°W., 66.0 ft., with a healed
double blaze.
A decayed fir stump, 40" dia. bears N.55°W., 32.3 ft. with
illegible scribe marks visible on open blaze. (Orig)
A fir, 5" dia., bears N.47°W., 7.9 ft., with illegible
scribe marks visible on partially healed blaze.
Corner is located S., 75 ft., of Bridge Creek Road, graveled
surface, 20 ft. wide, bears N.60°E. and S.60°W.