

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7351)

Set a yew post 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on West face; from which

A fir, 12" dia., bears S.58°E., 27 lks., mkd: ¼ S BT.

A fir, 14" dia., bears S.76°W., 25 lks., mkd: ¼ S BT.

Reported as not fd. DCSO VRT, 10/12/1965 - C.S. File 53/67-31

Wm. C. Stiles (Seek, Inc) - For: Moore Mill & Lbr. Co. - June 21, 1967 - C.S. File 55/44 & M34-19

Set at proportionate distance.

Set - 1"x30" galv. iron pipe, from which:

BTs - 9" W.Fir bears N.55°54'11"W., 22.3 ft. mkd: ¼ S8 BT.

7" W.Fir bears N.42°36'39"E., 29.0 ft. mkd: ¼ S9 BT.

BLM resurvey by George M. Winter, Cadastral Surveyor, under Group No. 2698, surveyed April 2013/Feb. 2014 - (DCSO records Vol. 58 page(s) 23155-6)

Point for the ¼ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original cor. Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd.

T30S R8W
¼
S 8|S 9
2013

from which

A fir, 11" dia., bears N.43°E., 30.6 ft., mkd. ¼ S9 BT.

A fir, 18" dia., bears N.65¼°W., 37.6 ft., mkd. ¼ S8 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor., a point established as the ¼ sec. cor. of secs. 8 and 9 by Stiles, in 1967, using improper procedure and was not utilized in the course of this survey, bears S.85°34'29"W., 3.21 ft., monumented with an iron pipe, 1½" dia., firmly set, projecting 4" above ground, from which the remains of a bearing tree mkd. by Stiles

A decayed hemlock snag, 12" dia., bears N.43¼°E., 29.1 ft., with scribe marks ¼ S9 visible on an open blaze.