

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor Secs 4 & 5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7353)  
-----  
Set a cedar post 3 ft. long, 3" sq., 18" in the ground, for 1/4 sec. cor., marked 1/4 S on W face; from which  
A cedar, 8" dia., bears S.45°E., 19 lks., mkd: 1/4 S BT.  
A fir, 50" dia., bears S.80°W., 16 lks., mkd: 1/4 S BT.

Reported as not fd, 4/8/1965 - DCSO, VRT - C.S. File 53/67-54

BLM dependent resurvey by Dale T. Bedell & Bryan S. Seibold, Cadastral Surveyors under Group No. 1494, surveyed July 1989/April 1993 - (DCSO records Vol. 50 (Page(s) 19023-4)  
-----  
Point for the 1/4 sec cor of secs 4 & 5, at proportionate dist; there is no remaining evidence of the original corner.  
Set a stainless steel post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd.  
T30S R8W  
1/4  
S 5 | S 4  
1990  
from which  
A hemlock, 18" dia. bears S.59 1/4°E., 31 1/2 lks. mkd. 1/4 S4 BT  
A G.Fir, 17" dia., bears S.77 1/2°W., 27 1/2 lks., mkd. 1/4 S5 BT.

Daniel A Renton, Minister-Glaeser Surveying - August Karlsen & Crew - For: US Department of Interior, BLM Beetle Battle North-Task C -May 10, 2023 - M178-73 A-D  
-----  
Found - 3 1/4" BLM brass cap (properly mkd) 0.8 ft above ground from which.  
An aluminum post with BLM boundary sign bears South 5 ft.  
An 18" stump bears S.62°E., 20.8 ft mkd "1/4 S4 BT" (1989)  
New - A 6" hemlock N.74°E., 6.3 ft. mkd: "1/4 S4 BT"  
A 4" hemlock S.22°W., 19.9 ft. mkd: "1/4 S5 BT"  
  
Set chaining nail at top center, BT sign on top and painted red band for existing BT  
  
Set chaining nail at side center, nail and washer stamped "PLS 2830" at base of blaze, BT signs on front and back and painted red band for new BTs.