

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5; 32 & 33, T29-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6577-78)

Set post cor. secs. 32, 33, 4 and 5, from which
A Cedar 15" dia., bears S.24°W., 30 lks. dist.
A Laurel 15" dia., bears N.62°E., 31 lks. dist.
A Laurel 12" dia., bears S.74°E., 33 lks. dist.
A Laurel 15" dia., bears N.50°W., 29 lks. dist.

Fd. and used in GL0 survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 16 Page(s) 6612)

A. Boyer - 1939 - C.S. File 16/25

Orig. Cedar, 30", S.24°30'W
Orig. Laurel, N.50°W., 19 ft.
30" Fir N.4½°E., 25 ft.
BT, S.9°E., 50 ft. on slope.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Oct. 29, 1958 - C.S. File 49/100-14

Found - Scribed stake set by Boyer in 1939.
Orig. Cedar now 32" dia., this had been chopped open to expose scribing "T30 R8W S5", can be plainly read.
Orig. Laurel now 24" bears N.46°W., (instead of N.50°W.) 19.1 ft. Center has entirely rotted away, but was rescribed by Boyer, scribing "S32 29S R8W CS & T" can be plainly read.
No trace found of other 2 orig. BTs.
30" Fir N.4½°E., 25 ft., bark scribed "S33 T29S R8W CS BT"
60" Fir S.9°E., 50 ft. on slope, bark scribed "S4 30/8 CS BT"

All distances measured from face of blaze.
Set Brass cap at cor. mkd: County Surveyors Office, 1958

T 29 S R 8 W
S 32 | S 33 T29S R8W
S 5 | S 4 T30S R8W

Blaze and scribe:
7" W.Fir N.36°W., 39.6 ft. mkd. T29S R8W S32 CS BT.

(Cont. Next Page)

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5; 32 & 33, T29-8

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Jan. 9, 1980 - M 79-15

Found - 1958 DCS0 brass cap/iron pipe.
36" Cedar bears S.23°W., 25.0 ft., 1882 survey.
36" Fir bears N.3°E., 25.0 ft. (Boyer ?)
56" Fir snag, bears S.13°E., 50.0 ft. (Boyer ?)

BLM Resurvey by Dale T. Bedell and Bryan S. Seibold, Cadastral Surveyors - Under Group #1494, Surveyed July 1989/April 1993 - (DCS0 records Vol. 50 Page(s) 19017)

The cor. of secs. 4, 5, 32, and 33, perpetuated by Boyer, in 1939, and recorded in Douglas County Surveyor's Office file No. 16/25, further perpetuated by Byron, in 1958, monumented with an iron post, 1½ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. in 1958 from which the remains of the original bearing trees

A cedar, 31 ins. diam., bears S. 24° W., 30 lks. dist., with scribe marks T30 R8W 5 visible on opened blaze.

A madrone snag, size indeterminate, bears N. 50° W., 29 lks. dist., no marks visible.

and the remains of bearing trees mkd. by Boyer

A fir, 34 ins. diam., bears N. 5½° E., 38½ lks. dist., with scribe marks S33 T29S R8W CS BT visible on a bark blaze.

A fir snag, 61 ins. diam., bears S. 10° E., 79 lks. dist., with scribe marks S4 30/8 CS BT visible on a bark blaze.

and the remains of a bearing tree mkd. by Byron

A fir snag, 17 ins. diam., bears N. 36° W., 60 lks. dist., with healed blaze.

and new bearing trees

A fir, 14 ins. diam., bears S. 37° E., 50½ lks. dist., mkd. T30S R8W S4 BT.

A fir, 16 ins. diam., bears N. 75° W., 135 lks. dist., mkd. T29S R8W S32 BT.

FD. & used on BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1972, surveyed April/May 2001- (DCS0 rec. Vol. 54 Page(s) 20955)