TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7347)

Set a chincapin post 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on North face; from which
A fir, 12" dia., bears N.20°E., 27 lks., mkd: ¼ S BT.
A chincapin, 5" dia., bears S.62°W., 8 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John Powell & crew - 6/1/1972 - C.S. File 53/67-16

Found - 12" now 22" D.Fir N.20°E., 17.8 ft. faint bark scribe visible "¼ "T"
5" now 11" chinquapin, S.62°W., 5.3 ft., opened for reverse scribe.

Set - brass cap at cor. mkd: COUNTY SURVEYORS T30S R8W OFFICE 1972 ¼ S 21 / S 28

New BTs- 11" W.Fir S.13°E., 27.3 ft. scribed "¼ S28 CS BT"
8" W.Fir N.2°W., 27.4 ft. scribed "¼ S21 CS BT"