

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7349)

Set a cedar post 3 ft. long, 3" sq., 18" in the ground, for 1/4 sec. cor., marked 1/4 S on North face; from which
A pine, 32" dia., bears S.45°W., 15 lks., mkd: 1/4 S BT.
A pine, 22" dia., bears N.50°E., 7 lks., mkd: 1/4 S BT.

Reported as not found by DCSO VRT 9/1965 - C.S. File 57/63-29

BLM dependent resurvey by G. Steven Popken & James J. Carlson, Cadastral Surveyors, Group No. 866, surveyed April/May. 1975 - (DCSO Vol. 39 Page(s) 15828)

Point for the 1/4 sec. cor. of secs. 16 & 21, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2 1/2" dia., 24" in the ground with brass cap marked:
T30S R8W
1/4 S 16
 S 21
1975
from which
A fir, 8" dia., bears N.71 1/2°E., 33 lks., mkd: 1/4 S16 BT.
A fir, 15" dia., bears S.11 1/2°W., 30 lks., mkd: 1/4 S21 BT.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2972, surveyed May 2020/Feb 2021 - (DCSO records Vol. 59 Page(s) 23963)

The 1/4 sec. cor. of secs. 16 and 21, reported by Popken and Carlson in 1975, monumented with an iron post, 2 1/2" dia., firmly set, with top flush with the surface of the ground, with a brass cap (properly) mkd.
from which the bearing tree reported by Popken and Carlson
A fir, 26" dia., bears S.11 1/2°W., 19.8 ft., with a healed blaze.
and a new bearing tree
A fir, 9" dia., bears N.46 1/2°W., 11.5 ft., mkd. 1/4 S16 BT.
Each new BT has a 2 1/2" x 1/4" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.