

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34; 3 & 4, T31-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7310)

Set a Fir post 4 ft. long, 4" sq., 20" in the ground for the cor. to secs. 3, 4, 33 and 34, mkd. T30S R8W S34 on the NE. face; T31S R8W S3 on the SE. face; S4 on the SW. face, and S33 on the NW. face. Also 3 notches on the E. and 3 notches on the W. angles of the same, and from which

A Fir 12" dia., bears N.40°E., 11 lks. dist. mkd. T30S R8W S34 BT.

A Fir 8" dia., bears S.39°E., 20 lks. dist. mkd. T31S R8W S3 BT.

A Fir 12" dia., bears S.30°W., 29 lks. dist. mkd. T31S R8W S4 BT.

A Fir 12" dia., bears N.58°W., 40 lks. dist. mkd. T30S R8W S33 BT.

BLM Resurvey by Charles E. Akin, Jr., Cadastral Surveyor under Group #795, Surveyed Aug/Sept. 1972 - (DCSO records Vol. 37 Page(s) 15225)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 30 S R 8 W
S 33 | S 34
S 4 | S 3
T 31 S
1972

from which

A Sugar Pine 15" dia., bears N.33½°E., 51 lks. dist. mkd. T30S R8W S34 BT.

A W.Fir 6" dia., bears S.22°E., 19½ lks. dist. mkd. T31S R8W S3 BT.

A W.Fir 8" dia., bears S.37½°W., 24 lks. dist. mkd. T31S R8W S4 BT.

A W.Fir 8" dia., bears N.49½°W., 32 lks. dist. mkd. T30S R8W S33 BT.

Tony Hostetter - For: Weyerhaeuser Co. - Nov. 2008 - M158-40

Found - Brass cap as set by BLM in 1972

12" W.Fir snag, face evident, BLM BT, bears S.22°E., 19.5 lks.

14" W.Fir snag face evident, BLM BT bears S.37½°W., 24 lks.

12" W.Fir stump, not marked, BLM BT bears N.49½°W., 32 lks. continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34; 3 & 4, T31-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 12" Fir, scribed "S34 SW BT" bears N.4°E., 27.6 ft to spike.
6" W.Fir, scribed "S4 NE BT" bears S.8°W., 27.2 ft. to spike.
10" Sugar pine, scribed "S33 SE BT" bears N.44°W., 37.7 ft. to spike.
16" cedar, scribed "S33 SE BT" bears N.28°W., 20.0 ft. to spike.

Gerald Nygren - For: Seneca Jones Timber - 4/2015 - M169-26

Found - 1972 BLM BC & BTs (2008) per (record)