

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor Secs 21, 22, 27 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7336-7)

Set a post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 21, 22, 27, & 28, marked T30S R8W S 22 on NE, S 27 on SE, S 28 on SW, S 21 on NW faces, with 2 notches on S & 3 notches on E edges; from which
A fir, 8" dia., bears N.33°E., 11 lks mkd: T30S R8W S22 BT
A fir, 9" dia., bears S.8°E., 10 lks. mkd: T30S R8W S27 BT
A fir, 8" dia., bears S.25°W., 28 lks mkd: T30S R8W S28 BT
A fir, 14" dia. bears N.71°W., 18 lks mkd: T30S R8W S21 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby & Jack Barnett - April 1965 - C.S. File 53/67-51

Found - Orig. 8" now 10" Fir N.33°E., 7.2 ft. tree face down & dead, scribe visible on opened face.
Orig. 8" now 16" Fir S.25°W., 18.5 ft. (alive) very old bark scribe visible "W T & part of S"
Orig. 14" now 33" Fir, N.71°W., 11.9 ft. (alive) shows "T R8W S2" bark scribe.
Set brass cap at cor. mkd: COUNTY SURVEYORS T30S R8W S21|S22
OFFICE 1965 S28|S27
New BTs- 8" cedar S.13°E., 35.6 ft. mkd: T30S R8W S27 CS BT.
16" D.Fir N.26°E., 16.6 ft. mkd: T30S R8W S22 CS BT.
Orig. 16" D.Fir S.25°W., 18.5 ft. mkd: T30S R8W S28 CS BT.

BLM dependent resurvey by G. Steven Popken & James J. Carlson, Cadastral Surveyors, Group No. 866, surveyed April/May. 1975 - (DCSO Vol. 39 Page(s) 15825-6)

The cor. of secs. 21, 22, 27, & 28, perpetuated and recorded by Byron, in 1965, monumented with an iron post, 1" dia., firmly set, projecting 10", above ground, with brass cap (properly) mkd.
from which the remains of the original BTs
A broken fir stump, 10" dia., bears N.33°E., 11 lks., with scribe marks TW visible on open blaze.
A fir, 21" dia., bears S.25°W., 28 lks., with healed double blaze. This tree was rescribed by Byron,
A root hole, bears N.71°W., 18 lks., with a down fir alongside, 33" dia., no marks visible.
and the remains of bearing trees mkd. by Byron
A fir, 16" dia., bears N.26°E., 25 lks., with healed double blaze.

continued next page

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A root hole, bears S.15°E., 54 lks., with a down cedar alongside, 7" dia., with scribe marks T30S R8W S27 CS BT visible on open double blaze.
and new bearing trees
A fir, 10" dia., bears S.82½°E., 56½ lks., mkd. T30S R8W S27 BT.
A fir, 30" dia., bears N.36½°W., 46 lks., mkd. T30S R8W S21 BT.

Kristian DeGroot - Sept. 1996 - M 125-51

Found - 1" iron pipe by Tracy in 1965 firmly set projecting 7" above the ground with a 2½" brass cap.
10" rotted fir stump, bears N.33°E., 7.3'
22" D.Fir, bears S.25°W., 18.5' with a healed blaze.
Root Hole, bears N.71°W., 11.9' with uprooted 33" Fir alongside.
Root Hole, bears N.26°E. 16.6' with an uprooted 18" D.Fir stump alongside with scribe marks visible.
Root hole, bears S.13°E., 35.6' with a rotted 7" Cedar alongside.
Root hole, bears S.82½°E., 37.3' with a partially uprooted 10" fir stump laying upside down and alongside.
Root hole, bears N.36½°W., 30.4' with an uprooted 30" D.Fir alongside with scribe marks "T30S R8W S21 BT" visible.

Douglas Co. Surveyors Office - Randall Smith, Stephen Flause;
Oct. 23, 1996 - C.S. File 65/9-31

Found - 2½" dia. DCSO brass cap on a 1½" O.D. iron pipe, protrudes 8" above ground.
8" now 22" dia. D.Fir with a fully healed double blaze, bears S.25°W., 19.0 ft. (rec. S.25°W., 18.5 ft. would go to orig. face.) O.B.T.
8" now 10" dia. 1 ft. high rotted D.Fir stump, no scribing visible, bears N.33°E., 7.9 ft. to center (rec. N.33°E., 7.2 ft.) O.B.T.
14" now 33" dia. tipped out of ground D.Fir, no scribing visible. Root hole agrees well with rec. "N.71°W., 11.9 ft." O.B.T.
16" now 18" dia. tipped out of position D.Fir stump, with a partially healed blaze, illegible scribing visible, root hole near rec. bearing and dist. "N.26°E., 16.6 ft."

continued next page

PRIMARY CORNER DESCRIPTION Cor Secs 21, 22, 27 & 28

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

	8" now 9" dia. tipped out of position and rotted Cedar root hole near rec. bearing and dist "S.13°E., 35.6 ft.
	10" now 10" dia. tipped out of position D.Fir stump, soil covered, no root hole. Rec. bearing & dist. "S.82½°E., 37.3 ft." 1975 BLM
	30" now 30" dia. tipped out of position D.Fir with an unhealed blaze, scribing visible "T30S R8W S21 BT" root hole near rec. bearing and distance "N.36½°W., 30.4 ft." 1975 BLM
New -	7" dia. Grand Fir, double blazed and scribed "T30S R8W S22 CS BT" bears N.72°E., 19.1 ft.
	18" dia. Cedar, double blazed and scribed "T30S R8W S21 CS BT" bears N.63°W., 24.2 ft.
	7" dia. D.Fir, double blazed and scribed "T30S R8W S27 CS BT" bears S.52°E., 44.2 ft.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2972, surveyed May 2020/Feb2021 - (DCSO records Vol. 59 Page(s) 23952-3)

The cor. of secs. 21, 22, 27, and 28, reported by Popken and Carlson in 1975; perpetuated by Smith, in 1996; monumented with an iron post, 1¼" dia. (Record, 1" dia.), firmly set, projecting 9" above ground, with a brass cap (properly) mkd. from which the remains of the bearing trees reported by Popken and Carlson

- A roothole bears N.26°E., 16.5 ft., alongside of which is an uprooted fir stump, 16" dia., with scribe marks S and other illegible scribe marks visible on open blaze.
- A decayed fir stump, 10" dia., bears N.33°E., 7.3 ft., no marks visible. (Original)
- A fir, 26" dia., bears S.25°W., 18.5 ft., with a healed blaze. (Original)
- A roothole bears N.71°W., 11.9 ft., alongside of which is a down decayed fir, size indeterminate, with a healed blaze. (Original)

and the bearing trees mkd. by Smith

- A fir, 18" dia., bears N.74¼°E., 18.7 ft., with a healed blaze.
- A fir, 14" dia., bears S.51½°E., 44.2 ft., with a healed double blaze.
- A cedar, 26" dia., bears N.62¾°W., 24.8 ft., with a healed double blaze.