TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7338)

Set a cedar post 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on West face; from which
A laurel, 10" dia., bears N.80°E., 12 lks., mkd: ¼ S BT.
A fir, 8" dia., bears N.36°W., 9 lks., mkd: ¼ S BT.

Reported as not found by DCSO, VRT 4/8/1965, C.S. 53/67-54

BLM dependent resurvey by G. Steven Popken & James J. Carlson, Cadastral Surveyors, Group No. 866, surveyed April/May. 1975 - (DCSO Vol. 39 Page(s) 15826-7)

The ¼ sec. cor. of secs. 21 & 22 determined at the record bearing & distance from each of the orig. BTs, as follows:
A fir snag, 8" dia., bears N.36°W., 9 lks., with scribe marks S BT visible on open blaze.
At the corner point
Set an iron post, 28 long, 2½" dia., 24" in the ground, with brass cap marked: T30S R8W

¼
S 21 | S 22
1975

from which new BTs
A fir, 20" dia., bears S.89°E., 39 lks., mkd: ¼ S22 BT.
A W.Fir, 20" dia., bears N.64°W., 67 lks., mkd: ¼ S21 BT.

Fd. Ok 9/1996 - K. DeGroot, M125-51

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2972, surveyed May 2020/Feb2021 - (DCSO records Vol. 59 Page(s) 23955)

The ¼ sec. cor. of secs. 21 and 22, reported by Popken and Carlson in 1975, monumented with an iron post, 2½" dia., firmly set, projecting 7" above ground, with a brass cap (properly) mkd.
from which the remains of BTs reported by Popken & Carlson
A fir, 26" dia., bears S.89°E., 25.7 ft., with a healed double blaze.
A fir, 29" dia., bears N.64°W., 43.3 ft., with a healed blaze. (Record, 44.2 ft.)
A decayed fir stump, 8" dia., bears N.36°W., 5.9 ft., no marks visible. (Original)
and a bearing tree mkd. by person(s) unknown
A fir, 26" dia., bears S.23¾°W., 8.4 ft., with a healed blaze.