

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7339-40)  
-----  
Set a Laurel post 3 ft. long, 3" sq., 18" in the ground, for 1/4 sec. cor., marked 1/4 S on West face; from which  
    A laurel, 5" dia., bears N.65°E., 48 lks., mkd: 1/4 S BT.  
    A laurel, 16" dia., bears S.44°W., 61 lks., mkd: 1/4 S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - M Godfrey & S.A. Bilow - Sept. 1958 - C.S. File 49/108-7  
-----  
Found - Laurel tree, now 22" dia., S.44°W., 40.3 ft. Upper blaze previously chopped open & face rotted, chopped out lower blaze & fd portions fo scribe mks on rotted face.  
    Dead laurel tree, now 9" dia., N.55°E., instead of N.65°E., 31.7 ft. Upper blaze previously chopped open & face rotted. Chopped out lower blaze & fd portions of scribe mks. on rotted face.  
At corner set iron pipe with brass cap mkd: COUNTY SURVEYORS OFFICE T30S R8W 1/4 S16|S15 - Erect mound of stones.  
Blaze & scribe: 15" D.Fir N.82 1/2°E., 24 ft. mkd: 1/4 S15 CS BT.  
                  15" D.Fir S.49°W., 30.7 ft. mkd: 1/4 S16 CS BT.

BLM retracement & rehabilitation by Kenneth W. Saveland, Cadastral Surveyor, under group No. 2300 dated March 16, 2007 - (DCSO records 2009 BLM Plat & Vol. 56 Page(s) 21839  
-----  
The 1/4 sec. cor. of secs. 15 & 16, monumented with an iron post, 1 1/4" dia., firmly set, projecting 15" above ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap (properly) mkd., from which the remaining Orig. BT  
    A madrone, 29" dia., bears S.44°W., 40.3 ft. with no marks visible on a hollow decayed blaze.  
and the remains of BTs mkd, by Byron in 1958  
    An uprooted sawed fir stump, 18" dia., bears N.83°E., 23.8 ft. with no marks visible  
    A roothole bears S.43 3/4°W., 31.3 ft. with fallen fir snag, 18" dia., lying alongside. with a healed double blaze.  
and a new BT  
    A fir, 14" dia., bears S.75 3/4°E., 19.2 ft, mkd: 1/4 S15 BT.  
Each new bearing tree has a 2 1/2"x 1/4" magnetic nail (Mag Nail) driven at the base right side-center.  
The geodetic position shown hereon was determined by a tie utilizing dual frequency carrier phase GPS receivers relative to the National Spatial Reference System. (NAD 1983 (CORS96))  
Latitude: 42°57'40.74"N                      Longitude: 123°38'33.40"W