

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor Secs 9, 10, 15, & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7340)

Set a cedar post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 9, 10, 15, & 16, marked T30S R8W S10 on NE, S 15 on SE, S16 on SW, S9 on NW faces, with 4 notches on S & 3 notches on E edges; from which
A Fir, 15" dia. bears N.28°E., 23 lks mkd: T30S R8W S10 BT
A fir, 16" dia. bears S.76°E., 17 lks mkd: T30S R8W S15 BT
A fir, 46" dia. bears S.36°W., 53 lks mkd: T30S R8W S16 BT
A cedar, 16" dia., bears N.28°W., 48 lks., mkd: T30S R8W S9 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - M Godfrey & S.A. Bilow - Aug. 1958 - C.S. File 49/108-3

Found - All orig. BTs
Orig. 16" now 36" cedar N.28°W., 31.7 ft. Shows faint scribe mks.
Orig. 15" now 36" fir stump N.28°E., 15.2 ft. I do not open good scar at base.
Orig. 46" now 48" Fir S.36°W., 34.9 ft. shows good bark scribing.
Orig. 16" now 36" Fir S.76°E., 11.2 ft. shows good bark scribing.
Set brass cap at cor. mkd: S 9|S10 T30S R8W COUNTY SURVEYORS
S16|S15 OFFICE 1958
New BTs- 10" W.Fir bears S.88½°W., 35.1 ft. scribed S16 T30S R8W CS BT.
Rescribe orig. now 36" cedar N.28°W., 31.7 ft. S9 T30S R8W CS BT.
10" R.Fir bears S.18½°E., 49.5 ft. scribed S15 T30S R8W CS BT.
8" R.Fir bears N.13°E., 32.8 ft. scribed S10 T30S R8W CS BT.

Ron Quimby - J. Leonard & N. Fromdahl - 5/8/2013 - C.S. File 65/78-37

Found - DCSO brass cap - poor condition.
22" Fir S.18½°E., 49.5 ft. scribed S15 T30S R8W CSBT
New - 16" W.Fir N.6°W., 9.5 ft. scribed S9 T30S R8W BT.
12" W.Fir S.68°W., 30.1 ft. scribed S16 T30S R8W BT.
10" W.Fir S.74°E., 20.9 ft. scribed S15 T30S R8W BT.
Note - Corner is on top of small N-S ridge 100'± south of old rd.

continued next page

1

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch
- June 11, 2013 - C.S. File 67/38-32

-
- Found - 2½" dia. brass cap (properly mkd) on a 1" I.D. iron pipe is somewhat loosely set protruding approx. 1½ ft. from ground but with top sharply bent and leaning approx. 0.7 ft. southwesterly from plumb.
- 4 OBTs - A fir, 15" dia., now 34" dia. 1½ ft. tall, sawn fir stump with possible burred blaze edge (no scribing remains); bears N.28°E., 16.0 ft. (rec. N.28°E. 15.2 ft is a reasonable face measurement)
- A fir, 16" dia., now 34" dia. 5 ft. tall fir stump fallen and out of position (did not examine for bark scribing) A very large and indistinct root-hole is near the record bearing and distance.
- A fir, 46" now a large but distinct root-hole with rotted fir root fragments; bears S.36°W., 35.0 ft. (as per rec.)
- A cedar, 16" dia., now a large indistinct root-hole with rotted cedar root fragments agrees reasonably with record B & D
- 1958 BTs- A 10" W.Fir now a very indistinct root-hole near record B & D
- A 10" R.Fir now a 22" dia., W.Fir no longer showing blaze evidence; bears S.19½°E., 49.5 ft. (rec. S.18½°E., 49.5 ft.)
- An 8" R.Fir now an 18" dia., 1½ ft. tall sawn fir stump with evidence of a low blaze (we open and find scribing "BT"); bears N.12°E., 32.8 ft. (rec. N.13°E., 32.8 ft.)
- 2013 BTs- A 16" W.Fir now a 16" dia., W.Fir scribed "S9 T30S R8W BT" on a single blaze; bears N.11°W., 9.0 ft. (rec. N.9°W., 9.5 ft.)
- A 12" W.Fir now a 12" dia., D.Fir scribed "S16T30SR8 BT" on a single blaze ("W" missing); bears S.66½°W., 30.1' ft. (rec. S.68°W., 30.1 ft)
- A 10" W.Fir now a 10" dia., D.Fir scribed "S15T30SR8W BT" on a single blaze; bears S.77½°E., 20.9 ft. (rec. S.74°E., 20.9 ft.)
- New - We reference plumb position of fd BC mon. & remove from ground. Pipe is straightened & BC monument is returned to plumb position. Monument is now firmly & plumbly set protruding 4" above ground. BT tags are corrected or added as needed. Monument and trees are flagged.
- Note - At top of low ridge (as described) in reprod forest of W.Fir, D.Fir & some cedar. Compass decl. 15½°E

cont. next pg

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor Secs 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Brent Knapp - Crew: N. Fromdahl, J. Ogden, & W. Keady -
6/12/2024 - C.S. file 65/113-38

Found - 1958 DCS0 brass cap (properly mkd)
17" W.Fir, N.11°W., 9.0'; with visible scar & BT tag.
11" W.Fir, S.77½°E., 20.9'; with visible scar and BT tag.
23" R.Fir, S.19½°E., 49.5'; with visible scar and BT tag.
16" W.Fir, S.66½°W., 30.1'; with visible scar and BT tag.
18"x1.5' tall stump N.12°E., 32.8' with visible scar and BT tag.
34"x1.5' tall stump N.28°E., 16.0' with BT tag.
Root Hole S.36°W., 35.0'.
Note - Compass decl. 15°E.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and
Jeff Lorsung - 1/27/2025 - C.S. File 67/59-54

Found ok.
OCRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
N. 49441.300 E. 81282.306