TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7341)

Set a cedar post 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on West face; from which
A fir, 14" dia., bears S.62°E., 13 lks., mkd: ¼ S BT.
A chincapin, 5" dia., bears West, 34 lks., mkd: ¼ S BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby & Jack Barnett - April 1965 - C.S. File 53/67-47

Found - 14" now 28" fir S.62°E., 8.6 ft. "¼ S BT" bark scribe.
5" now 6" chinquapin West 22.4 ft. mostly rotted away, found partial face with possible reverse scribe "1"
Set brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1965
T30S R8W ¼ S9|S10
New BTs- 8" D.Fir S.38°W., 32.0 ft. mkd: ¼ S9 CS BT.
16" D.Fir S.26°E., 36.8 ft. mkd: ¼ S10 CS BT.

Fd. OK by R. Quimby, 5/8/2013 - C.S. File 65/78-39

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 1/27/2025 - C.S. File 67/59-53

Found - 2½" DCSO brass cap (prop mkd)Cap proj 4"
32" D.Fir S.62°E. 8.6'
16" D.Fir S.38°W. 32.0'
30" D.Fir S.26°E. 36.8'
New - 24" W.Fir N.4°W. 30.4' marked ¼ S9 BT on unhealed single blaze by Roseburg Resources 4-24
Notes - Comp Dec 14¼°E.
OCRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
N. 52073.582 E. 81281.761