

PRIMARY CORNER DESCRIPTION Cor. Secs 3, 4, 9 & 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7341-2)  
-----  
A fir tree, 60" dia., which I marked T30S R8W S3 on NE, S10 on SE, S9 on SW & S4 on NW faces, with 5 notches on South & 3 notches on East edges for cor. to secs. 3, 4, 9 & 10, from which  
    A chincapin, 10" dia., bears N.80°E., 35 lks., mkd: T30S R8W S3 BT.  
    A fir, 5" dia., bears S.45°E., 25 lks., mkd: T30S R8W S10 BT.  
    A chincapin, 5" dia., bears S.67°W., 41 lks., mkd: T30S R8W S9 BT.  
    A chincapin, 5" dia., bears N.30°W., 7 lks., mkd: T30S R8W S4 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby & Jack Barnett - April 1965 - C.S. File 53/67-55  
-----  
Found - 60", now 62" Corner Tree alive with bark scribe "T30S R8W S3" on NE side & "S" bark scribe on NW side.  
    No Orig. BTs remain.  
Set - Brass Cap at Cor. 10 ft. S for Wit. Cor. & Mkd:  
    County Surveyor's T30S WC 10 ft N.  $\frac{S \ 4 \ S \ 3}{S \ 9 \ S \ 10}$  R8W Office, 1965  
New BTs- 8" D.Fir East 55.5 ft. Mkd: WC T30S R8W S3 CS BT.  
    13" Chinq. N.45°W. 44.4 ft. mkd: WC T30S R8W S4 CS BT.  
    12" W.Fir S.63°W., 26.5 ft. mkd: WC T30S R8W S9 CS BT.  
    8" Hemlock S.35°E., 38.5 ft. mkd: WC T30S R8W S10 CS BT.

BLM dependent resurvey by Wayne L. Rogers, Lance J. Bishop, and James L. White, Cadastral Surveyors under Group No. 1240 surveyed Feb/July 1985 - (DCSO records Vol. 47 Pages 18110-1)  
-----  
The cor, of secs. 3, 4, 9, & 10, perpetuated & recorded by Tracy, in 1965, monumented by the orig. corner tree, a fir snag, 62" dia., with scribe marks T30S R8W S3 visible on bark blaze on NE. face, from which new BTs:  
    A hemlock, 6" dia., bears N.80°E., 73 lks., mkd. X BT.  
    A fir, 4" dia., bears S.42½°E., 35 lks., mkd. X BT.  
    A G.Fir, 19" dia., bears S.21°W., 76 lks., mkd. T30S R8W S9 BT.  
continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor Secs 3, 4, 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A G.Fir, 9" dia., bears N.51¼°W., 44 lks., mkd. T30S R8W S4 BT.  
From this point, a witness corner established and recorded by Tracy, in 1965, bears South, 0.15 chs., monumented with an iron post, 1¼" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd. from which the bearing trees mkd. by Tracy  
A fir, 11" dia., bears S.87°E., 84 lks., with healed double blaze.  
A hemlock, 15" dia., bears S.35°E., 58 lks., with healed double blaze.  
A G.Fir, 19" dia., bears S.55°W., 42 lks., with healed double blaze.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2300, Surveyed March/April 2010 - (DCS0 records BLM Plat 2011-3 & Vol. 57 Page(s) 22688)

-----  
The cor. of secs. 3, 4, 9 and 10, monumented with the original corner tree, a fir snag, 62" dia., with scribe mark W and other fragmentary scribe marks visible on the bark of the NE. face, with axe marks and notches around base of trunk, from which BTs mkd. by Rogers, Bishop, and White  
A hemlock, 11" dia., bears N.80°E., 48.2 ft., with a healed double blaze.  
A fir, 11" dia., bears S.42½°E., 23.1 ft., with a healed double blaze.  
A fir, 25" dia., bears S.21°W., 50.2 ft., with a healed blaze.  
A fir, 15" dia., bears N.51¼°W., 29.0 ft., with a healed blaze.  
and new reference monuments  
Drive a rebar, 30" long, 5/8" dia., 28" in the ground, bears S.65°51'58"E., 28.95 ft., with aluminum cap mkd. RM T30S R8W S10 29.0 FT TO COR 2010 and an arrow pointing to the corner.  
Drive a rebar, 30" long, 5/8" dia., 28" in the ground for a reference monument, bears S.22°46'58"W., 25.76 ft., with aluminum cop mkd. RM T30S R8W S9 25.8 FT TO COR 2010 and an arrow pointing to the corner.  
From this corner, a WC established by the Douglas Co. Surveyor's Office in 1965, bears South, 9.90 ft., monumented with on iron post, 1¼" dia., firmly set, projecting 6" above ground, with a brass cap (properly) mkd. from which BTs mkd. by the Douglas County Surveyor's Office

continued next page

2

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 16" dia., bears S.87°E., 54.2 ft., with a healed blaze. (Record, 55.4 ft.)  
A hemlock, 20" dia., bears S.35°E., 38.3 ft., with a healed blaze.  
A fir, 25" dia., bears S.62¾°W., 27.7 ft., with a healed blaze. (Record, S.55°W.)  
and the remains of a BT mkd. by the Douglas County Surveyors Office, not previously reported by Rogers, Bishop, and White  
A roothole bears N.45¼°W.. 43.8 ft., alongside of which is an uprooted chinquapin root crown, size indeterminate, with no marks visible.

Fd. Witness monument to sec. cor. fd as per 2011 BLM resurvey, 2/2013 by D. Edwards, C.S. File 65/79-2