

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 402700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only, T 29-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6577)

Set post cor. secs. 33, 34, 3 and 4, from which
A Laurel 15" dia., bears S.20°E., 35 lks. dist.
A Laurel 10" dia., bears S.10°W., 33 lks. dist.
A Laurel 10" dia., bears N.18°E., 34 lks. dist.
A Laurel 12" dia., bears N.36°W., 25 lks. dist.

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 16 Page(s) 6611)

Old cor. to secs. 3, 4, 33 and 34, which is a post 4" sq., firmly set in the ground and mkd. T29S S34 on NE.; T30S S3 on SE.; R8W S4 on the SW.; and S33 on the NW. faces of same and from which
(Found trees as described above)

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Jan. 9, 1980 - M 79-15

Set 5/8" x 48" Iron rod and alum. cap, from which
22" Fir bears N.60½°W., 16.7 ft.
14" Fir N.28°E., 46.6 ft.
26" Fir S.20°E., 44.9 ft.

Fd. & used on BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1972, surveyed April/May 2001- (DCSO rec. Vol. 54 Page(s) 20952)