

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7339)  
-----  
Set a post 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on North face; from which  
A hemlock, 15" dia., bears S.40°E., 16 lks., mkd: ¼ S BT.  
A fir, 48" dia., bears N.44°E., 40 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - M Godfrey & S.A. Bilow - Aug. 1958 - C.S. File 49/108-4  
-----  
Found - Orig. 48" now 50" R.Fir snag N.44°E., 26.4 ft. Shows old bark scribing "¼" & recent bark scribe ¼ S.  
No trace of orig. SE BT  
Set brass cap at corner mkd: ¼ S 15 T30S R8W County Surveyors  
S 22 Office 1958  
New BTs- 7" R.Fir bears S.16°W., 27.5 ft. scribed ¼ S22 CS BT  
8" R.Fir bears N.22½°E. 30.8 ft. scribed ¼ S15 CS BT

Fd. Ok 9/1996 - K. DeGroot, M125-51

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2972, surveyed May 2020/Feb2021 - (DCSO records Vol. 59 Page(s) 23957)  
-----  
The ¼ sec. cor. of secs. 15 and 22, perpetuated by Byron, in August 1958; monumented with an iron post, 1¼" dia., firmly set, projecting 15" above ground, with a brass cap(properly) mkd  
from which the remains of an original bearing tree  
A decayed fir snag, 38" dia., bears N.44°E., 26.4 ft., no marks visible.  
and the remains of the bearing trees mkd. by Byron  
A decayed fir snag, 13" dia., bears N.22¾°E., 31.4 ft., with a healed double blaze.  
A fir, 27" dia., bears S.66°E., 27.3 ft., with a healed blaze.  
and a new bearing tree  
A fir, 11" dia., bears N.57¼°E., 22.4 ft., mkd. ¼ S15 BT.  
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.