TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7341)

Set a cedar post 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on North face; from which
A laurel, 14" dia., bears North, 25 lks., mkd: ¼ S BT.
A laurel, 10" dia., bears S.54°W., 24 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby & Jack Barnett - Sept. 1964 - C.S. File 53/67-58

Found - 2"x2"x4' sq. post & 14" now 24" laurel North 16.5 ft. shows faint "T" scribe.
10" laurel S.54°W., 15.8 ft. down & mostly rotted away, found ">" reverse scribe.
Set brass cap at cor. mkd: COUNTY SURVEYORS T30S R8W ¼ S 10
OFFICE 1964 S 15
New BTs- 6" D.Fir N.16°W., 38.1 ft. mkd: ¼ S10 CS BT.
16" D.Fir S.39°E., 17.5 ft. mkd: ¼ S15 CS BT.

Ron Quimby - J. Leonard & N. Fromdahl - 5/8/2013 - C.S. File 65/78-37

Found - DCSO brass cap
17" D.Fir stump S.39°E., 17.5 ft.
24" madrona N.10°W., 16.5 ft., visible scribes, no record.
6" D.Fir down & rotted.
New - A 10" W.Fir S.9°E., 14.6 ft. scribed ¼ S15 BT.
Note - On steep east facing hillside on edge of reprod unit 350'± east of landing @ end of road.