

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7342)

Set a cedar post 3 ft. long, 3" sq., 18" in the ground, for 1/4 sec. cor., marked 1/4 S on North face; from which
A cedar, 12" dia., bears S.12°W., 20 lks., mkd: 1/4 S BT.
A yew, 5" dia., bears N.10°E., 29 lks., mkd: 1/4 S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Ray Tracy & Mike Stone - Oct. 12, 1965 - C.S. File 53/67-30

Found - Orig. 5", now 12" Yew N.10°E. 19.1 ft., very old face apparently never healed, shows poor "1/4" scribe lower face very badly rotted, BT. alive but in poor condition.
Orig. 12", now 17" Cedar Snag S.12°W. 13.2 ft., burned face, no scribe found.
Set brass Cap at Cor. Mkd: County Surveyors T30S R8W 1/4 S 3
Office, 1965 S 10
New BTs- 8" D.Fir S.39°W. 23.2 ft. mkd: 1/4 S10 CS BT.
9" Hemlock N.32°E. 40.7 ft. mkd: 1/4 S3 CS BT.
Note - This corner lies approx. 300 ft. West of creek, flowing NE.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2300, Surveyed March/April 2010 - (DCSO records BLM Plat 2011-3 & Vol. 57 Page(s) 22688)

The 1/4 sec. cor. of secs. 3 and 10 perpetuated by Byron, in 1965, monumented with an iron post, 1 1/4" dia., firmly set, projecting 16" above ground, with a brass cap (properly) mkd. from which the remains of the original bearing trees
A yew. 3" dia., bears N.10°E., 19.1 ft. with no marks visible.
A sawed, hollow, and burnt cedar stump, 15" dia., bears S.12°W., 13.2 ft., with no marks visible.
and the remains of bearing frees mkd. by Byron
A decayed hemlock snag. 13" dia., bears N.32 1/2°E, 40.8 ft., with fragmentary scribe marks visible on a partially healed double blaze,
A fir, 19" dia., bears S.38 3/4°W., 23.4 ft., with a healed blaze.
Lat: 42°58'59.37"N Long: 123°37'58.93"W (NAD 1983 (CORS 96))