

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7311)

Set a Fir post 4 ft. long, 4" sq., 20" in the ground for the cor. to secs. 2, 3, 34 and 35, mkd. T30S R8W S35 on the NE. face; T31S S2 on the SE. face; S3 on the SW. face and S34 on the NW. face. Also 2 notches on the E. and 4 notches on the W. angles of the same, and from which

- A Laurel 6" dia., bears N.38°E., 12 lks. dist. mkd. T30S R8W S35 BT.
- A Fir 12" dia., bears S.78°E., 71 lks. dist. mkd. T31S R8W S2 BT.
- A Laurel 10" dia., bears S.14°W., 62 lks. dist. mkd. T31S R8W S3 BT.
- A Laurel 5" dia., bears N.50°W., 34 lks. dist. mkd. T30S R8W S34 BT.

BLM Resurvey by Charles E. Akin, Jr., Cadastral Surveyor under Group #795, Surveyed Aug/Sept. 1972 - (DCSO records Vol. 37 Page(s) 15224)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 30 S R 8 W
S 34 | S 35
S 3 | S 2
T 31 S
1972

from which

- A W.Fir 8" dia., bears N.79½°E., 53 lks. dist. mkd. T30S R8W S35 BT.
- A W.Fir 6" dia., bears S.76°E., 10½ lks. dist. mkd. T31S R8W S2 BT.
- A Fir 6" dia., bears S.6½°W., 23½ lks. dist. mkd. T31S R8W S3 BT.
- A Fir 6" dia., bears N.74°W., 77 lks. dist. mkd. T30S R8W S34 BT.

Fd. OK, Jan. 2002 by T. Rambo - M139-47
Fd. OK, July 2007 by T. Rambo - M153-45
FD. Ok Nov. 2008 by T. Hostetter - M158-40

continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35; 2 & 3, T31-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2192, Surveyed June/July 2008 - (DCSO records Vol. 56 Page(s) 22145)

The cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with an iron post, 2½" dia., firmly set, projecting 6" above the ground, with brass cap (properly) mkd from which bearing trees mkd. by Akin

- A fir, 19" dia., bears N.79½°E., 35.0 ft., with a healed blaze.
- A fir, 13" dia., bears S.76°E., 6.9 ft., with a healed blaze.
- A fir, 10" dia., bears S.6½°W., 15.5 ft., with a healed blaze.
- A fir, 10" dia., bears N.74°W., 50.8 ft., with a healed blaze.