

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor Secs 26, 27, 34, & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7326)  
-----  
Set a cedar post 4 ft. long, 4" sq., 24" in the ground for the corner to Secs. 26, 27, 34, & 35, marked T30S R8W S26 on the NE, S35 on SE, S34 on SW, and S27 on the NW face, with 1 notch on S and 2 notches on E edges, and from which  
A fir, 10" dia. bears N.50°E., 48 lks mkd: T30S R8W S26 BT  
A fir, 24" dia. bears S.45°E., 13 lks mkd: T30S R8W S35 BT  
A fir, 8" dia., bears S.10°W., 14 lks mkd: T30S R8W S34 BT  
A fir, 12" dia., bears N.8°W., 6 lks. mkd: T30S R8W S27 BT

A.R. Evans - For: Martin Box Co. - June 6, 1955 - C.S. 42/21  
-----  
Set a 4"x4"x36" cedar stake  
Blaze & scribe 4 BTs  
A 46" D.Fir, N.84°E., 75.1 ft. mkd: T30-R8, S26-RE 2741 BT  
A 30" D.Fir N.43¼°W., 19.5 ft. mkd: T30-R8, S27-RE 2741 BT  
A 24" D.Fir S.19°W., 19.6 ft. mkd: T30-R8, S34-RE 2741 BT  
A 33" D.Fir S.42½°E., 80.7 ft. mkd: T30-R8, S34-RE 2741 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby & Jack Barnett - April 1965 - C.S. File 53/67-45  
-----  
Found - 46" D.Fir N.84°E., 75.1 ft. shows "T30SR8WS26 RE2741 BT"  
30" D.Fir N.43¼°W., 19.5 ft blaze mostly healed over  
24" D.Fir S.19°W., 19.6 ft. partial scribe visible on pitched over blaze.  
33" D.Fir S.42½°E., 80.7 ft. shows T30SR8W S35 RE2741BT" bark scribe. All four BTs above rec. in (1955) ren.  
No orig. BTs evident at this time.  
Set BC at cor mkd: COUNTY SURVEYORS T30S R8W S 27|S26  
OFFICE 1965 S 34|S 35  
No new BTs required. Corner lies in cutting corner area cut off in Sec. 26.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - Feb. 27, 1984 - C.S. File 62/16-19  
-----  
Found - I.P. w/County B.C. as per 1965 ren  
46" D.Fir N.84°E, is down w/a visible blaze showing.  
30 D.Fir, now a 30" diam. 12 ft. high snag bears N.46°W. (Rec. is N.43¼°W.) 20.6 ft. (Rec. 19.5 ft. is to face). A healed single blaze has a partial scribing visible.  
continued next page

Alias	Description
Alias	Description
Alias	Description
Alias	Description

24" D.Fir, now a 24" diam. 8 ft. high stump bears S.19°W., 20.1 ft. (Rec. 19.6 ft.) partially healed blaze has some scribing visible: "S R R E 2 7 4 BT".

33" D.Fir, now a 33" dia. 24" high stump, bears S.42½°E., 81.9 ft. (Rec. 80.7 ft. is to face).

New BTs- 11" W.Fir dbl. blazed & scribed: "T30S R8W S26 CS BT" bears N.42½°E., 5.9 ft.

6" W.Fir, dbl. blazed & scribed: "T30S R8W S27 CS BT" bears N.42°W., 29.0 ft.

10" W.Fir, dbl. blazed & scribed: "T30S R8W S34 CS BT" bears S.88°W., 55.0 ft.

New B0 - Set a 1/2"x8" spike in a 33" D.Fir stump, which bears S.42½°E., 81.9 ft. Spike is set through a DCS0 bearing tree tag in top of stump. (stump is a BT per 1955 Ren.) Spike is stamped B0 1.

See sketch in file.

Fd. Ok by D. Edwards, 2/2005 - C.S. File 65/55-1. Set 6' post 2' north.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2192, Surveyed June/July 2008 - (DCS0 records Vol. 56 Page(s) 22150-1)

-----

The cor. of secs. 26, 27, 34, & 35, perpetuated by Evans, in 1955, as the position of the original cor. indicated in an affidavit signed by Jack Chapman, subsequently perpetuated by Douglas Co. Surveyor's Office in 1965, further perpetuated by Smith, in 1984, & further perpetuated by Edwards, monumented with an iron post, 1¼" diam. firmly set, projecting 5" above the ground, with brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Evans

A roothole bears N.85½°E., 76.2 ft., alongside of which is a down, decayed, fir snag, size indeterminate, with a healed blaze.

A sawed fir stump, 38" dia., bears S.43¼°E., 81.9 ft., with no marks visible on a hollow blaze, and the head of a spike driven flush with top and in the center of the stump, mkd. B0 1.

A decayed fir snag, 19" dia., bears S.19¾°W., 20.6 ft., with fragmentary scribe marks visible on a partially healed blaze.

A fir snag, 33" dia., bears N.44½°W., 20.3 ft., with a healed blaze.

and the remains of bearing trees mkd. by Smith

continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor Secs 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir stump, 18" dia., bears N.42¾°E., 6.0 ft., alongside of which is a down fir snag, 18" dia., with a healed blaze.

A fir, 17" dia., bears S.87¾°W., 54.6 ft., with a healed blaze.

A roothole bears N.42¾°W., 28.9 ft., alongside of which is a down, decayed fir snag, size indeterminate, with fragmentary scribe marks visible on an opened blaze.

and bearing trees mkd. by Edwards

A fir, 10" dia., bears N.70½°E., 24.0 ft., with a healed blaze.

A fir, 13" dia., bears S.37½°E., 17.3 ft., with a healed blaze.

and a new bearing tree

A fir, 6" dia., bears N.86½°W., 21.2 ft., mkd. T30S R8W S27 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2972, surveyed May 2020/Feb2021 - (DCS0 records Vol. 59 Page(s) 23949-50)

-----

The cor. of secs. 26, 27, 34, and 35, reported by Saveland in June through July of 2008, monumented with an iron post, 1¼" dia., firmly set, projecting 5" above ground, with a brass cap (properly) mkd.

from which the remains of the BTs reported by Saveland

A roothole bears N.42¾°E., 6.0 ft., alongside of which is a down fir, size indeterminate, no marks visible.

A broken fir stump, 12" dia., bears N.70½°E., 24.0 ft., alongside of which is a down fir, 12" dia., with scribe marks S26 BT and other illegible scribe marks visible on partially healed blaze.

A decayed fir stump, 38" dia., bears S.43¾°E., 81.9 ft., no marks visible, and the head of a spike driven flush with top and in the center of the stump, mkd. B0 1.

A fir, 17" dia., bears S.37½°E., 17.3 ft., with a healed blaze.

A decayed fir stump, size indeterminate, bears S.19¾°W., 20.6 ft., with scribe marks T30S R W S visible on broken fragment lying alongside.

A fir, 21" dia., bears S.87¾°W., 54.6 ft., with a healed blaze.

A fir, 10" dia., bears N.86½°W., 21.2 ft., with a healed blaze.

A decayed fir snag, 33" dia., bears N.44½°W., 20.3 ft., with a healed blaze.

Continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor Secs 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a new bearing tree

A fir, 15" dia., bears N.57¾°E., 32.4 ft., mkd. T30S R8W S26 BT.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.

NAD 1983 (2011)

Latitude: 42°55'34.70" N.      Longitude: 123°37'25.20" W.