

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7327)

Set a sand stone 16x14x8", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
 A fir, 12" dia., bears N.75°W., 6 lks., mkd: ¼ S BT.
 A laurel, 11" dia., bears S.20°E., 21 lks., mkd: ¼ S BT.

Reported as not fd by V.R. Tracy, 4/1965, C.S. File 53/67-52

Howard W. Johnstone - For: Roseburg Lumber Co. - June 30, 1982 - M 92-52

Found no evidence of the orig. corner.
Set - 5/8"x36" IR & alum. cap mkd: LS 498
New - 6" fir bears S.40°E., 13.5 ft. (scribed)
 12" fir bears N.49°W., 45.4 ft. (scribed)

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2192, Surveyed June/July2008 - (DCSO records Vol. 56 Page(s) 22153)

The ¼ sec. cor. of secs. 26 & 27, reestablished by Johnstone at proportionate dist. There is no remaining evidence of the original cor., therefore this position is accepted as the best available evidence of the original cor., monumented with an iron rebar, 5/8" dia., firmly set, projecting 12" above ground, with aluminum cap (properly) mkd. from which bearing trees mkd. by Johnstone
 A fir, 9" dia., bears S.42°E., 13.6 ft., with a healed blaze.
 A fir, 18" dia., bears N.49¾°W., 45.5 ft., with a healed blaze.