

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7330)

-----

Set a fir post, 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on W face; from which

A fir, 12" dia., bears N.65°W., 70 lks., mkd: ¼ S BT.

A fir, 5" dia., bears S.78°E., 36 lks., mkd: ¼ S BT.

BLM dependent resurvey by Donald R. Beck & C. Albert White, Cadastral Surveyor, under group #350 & 548, surveyed May 1963/July 1964 - (DCSO records Vol. 32 Page(s) 13599)

-----

Point for the ¼ sec. cor. of secs. 14 & 15, at proportionate distance; there is no remaining evidence of the orig. corner.

Set an iron post, 28 long, 2½" dia., 21" in the ground with brass cap marked:

T30S R8W

¼

S 15|S 14

1964

from which

A fir, 20" dia., bears N.43¾°E., 51 lks., mkd: ¼ S14 BT.

A fir, 10" dia., bears N.65°W., 49 lks., mkd: ¼ S15 BT.