

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs 10, 11, 14, & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7331)

Set a stone 14x10x5", 9" in the ground for cor. of secs. 10, 11, 14, & 15 mkd with 4 notches on S & 2 notches on E edges, from which
A fir, 24" dia. bears N.28°E., 74 lks mkd: T30S R8W S11 BT
A fir, 24" dia. bears S.49°E., 78 lks mkd: T30S R8W S14 BT
A laurel, 14" dia., bears S.24°W., 35 lks., mkd: T30S R8W S15 BT.

Howard W. Johnstone - For: Roseburg Lumber Co. - May 28, 1962 - C.S. File 51/163-3

Found - Original Corner Stone
Set - 1/2" by 30" Iron Pipe.
Scribed- 24" Cedar S.19°E. 69.0 ft.
- 6" D.Fir S.52½°W. 28.3 ft.
- 48" D.Fir N.84°E. 108.0 ft.
- 48" D.Fir N.43°W. 23.0 ft.
The N.43°W. tree is Orig. BT. but wasn't recorded, bark scribe)

BLM dependent resurvey by Donald R. Beck & C. Albert White, Cadastral Surveyor, under group #350 & 548, surveyed May 1963/July 1964 - (DCSO records Vol. 32 Page(s) 13599-1300)

The cor. of secs. 10, 11, 14, and 15, monumented with the original basalt stone, 14x10x5", firmly set, 6" in the ground, with 4 grooves on the S side, & 2 grooves on the S side, alongside which is an iron pipe, 1/2" dia., 10" above ground, set and recorded by Johnstone, in 1962, from which the remains of the original bearing trees
A fir, 42" dia., bears N.31°E., 74 lks., with old axe mks. and a recent blaze. (Record bearing, N.28°E.)
A fir, 41" dia., bears S.51°E., 82 lks., with old axe mks. and a recent blaze. (Record, S.49°E., 78 lks.)
A madrone stump hole, bears S.28°W., 37 lks., (Record, S.24°W., 35 lks.)
and bearing trees by Johnstone
A fir, 17" dia., bears N.83¼°E., 163 lks., with a partially healed double blaze.
A cedar, 24" dia., bears S.20½°E., 105 lks., mkd. T30S R8W S14 BT on double blaze,
A fir, 7" dia., bears S.50½°W., 40 lks., with a partially healed double blaze.
and a bearing tree of which I find no record
continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 50" dia., bears N.43°W., 35 lks., mkd. 3 R8W BT, remarked T30S R8W S10 BT on bark blaze by Johnstone. (The old scribe mks. appear to be of the same age and characteristics of the 1882 survey.)

At the corner point

Set an iron post, 28" long, 2½" dia., 25" in the ground, with brass cap mkd.

T30S R8W	
S 10	S 11
S 15	S 14
1964	

from which a new bearing tree

A fir, 8" dia. bears N.87¾°W. 106 lks mkd. T30S R8W S10 BT
Deposit original corner stone and reset iron pipe alongside iron post.