

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7332)

Set a stone 14x8x6", 1" in the ground for 1/4 sec. cor. mkd. 1/4 on W face, from which

A fir, 32" dia., bears N.85°E., 40 lks., mkd: 1/4 S BT.

A laurel, 9" dia., bears S.9°W., 62 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Donald R. Beck & C. Albert White, Cadastral Surveyor, under group #350 & 548, surveyed May 1963/July 1964 - (DCSO records Vol. 32 Page(s) 13602)

Point for the 1/4 sec. cor. of secs. 10 & 11, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 14 long, 1" dia., 4" in drill hole in solid rock with brass cap marked: T30S R8W

1/4
S 10 | S 11
1964

from which

A fir, 9" dia., bears S.27°E., 61 lks., mkd: 1/4 S11 BT.

A cedar, 8" dia., bears N.3 1/2°W., 89 lks., mkd: 1/4 S10 BT.