

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7332)

-----  
Set a stone 15x12x12", in the ground for cor. of secs. 2, 3, 10, & 11 mkd with 5 notches on S & 2 notches on E edges, from which

- A fir, 15" dia., bears N.39°E., 54 lks mkd: T30S R8W S2 BT
- A maple, 7" dia., bears S.47°E., 47 lks., mkd: T30S R8W S11 BT.
- A maple, 10" dia., bears S.15°W., 52 lks., mkd: T30S R8W S10 BT.
- A fir, 10" dia., bears N.15°W., 54 lks mkd: T30S R8W S3 BT

BLM dependent resurvey by Donald R. Beck & C. Albert White, Cadastral Surveyor, under group #350 & 548, surveyed May 1963/July 1964 - (DCSO records Vol. 32 Page(s) 13602-3)

-----  
The cor. of secs. 2, 3, 10, & 11, monumented with the orig. basalt stone, 18x16x10" loosely set, 3" in the ground, with 5 grooves on the S & 2 grooves on the E face, from which the remaining orig. BTs:

- A rotted maple stump, 10" dia., bears S.38°E., 47 lks., with no marks visible. (Rec. S.47°E.)
- A rotted fir stump, 20" dia., bears N.15°W., 54 lks., with no marks visible.

At the corner point

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

T30S	R8W
<u>S 3</u>	<u>S 2</u>
S 10	S 11
1964	

from which new BTs

- A cedar, 8" dia., bears N.20°E., 117 lks., mkd: T30S R8W S2 BT.
- A fir, 6" dia., bears S.22¾°E., 128 lks., mkd: T30S R8W S11 BT.
- A fir, 40" dia. bears S.45°W., 31 lks mkd: T30S R8W S10 BT
- A fir, 33" dia. bears N.53°W., 20 lks. mkd: T30S R8W S3 BT

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, under Group No. 2300: Admin. file #0906, surveyed July 2006/May 2007 - (DCSO recs Vol 56 Pg 22319 & Plat T30-8 2011)

-----  
The cor. of secs. 2, 3, 10 & 11, monumented with an iron post, 2½" dia., firmly set, projecting 5" above ground, with brass cap (properly) mkd.

from which the remains of BTs mkd. by Beck & White in 1963-1964  
continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A roothole bears S.45°W., 20.5 ft., with uprooted, sawed fir stump, 45" dia., lying alongside, no marks visible.  
A decayed sawed fir stump, 32" dia., bears N.53°W., 13.2 ft., with fragmentary scribe marks visible on a partially healed blaze.  
and new bearing trees  
A fir, 12" dia. bears N.42½°E., 7.8 ft. mkd T30S R8W S2 BT  
A fir, 12" dia., bears S.16¾°E., 62.9 ft., mkd T30S R8W S11 BT.  
A fir, 12" dia.. bears S.42½°W., 25.2 ft., mkd T30S R8W S10 BT.  
A fir, 10" dia. bears N.68½°W., 31.4 ft mkd T30S R8W S3 BT  
The geographic position (NAD 1983 (CORS96)) of the corner of sections 2, 3, 10, and 11, was determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online User Positioning Service.  
Latitude 42°59'00.14"N  
Longitude 123°37'24.67"W  
(NAD 1983 (CORS 96))