

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION C.C. for Secs. 2 & 3 only, (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 16 Page(s) 6610)

Set a Cedar triangular post 4" dia., 4 ft. long, 20" in the ground mkd. T29S R8W S34 on N.; T30S R8W S2 on the SE.; S3 on the SW. Also 2 notches on the E. and 4 notches on the W. angles of same, and from which

A Fir 40" dia., bears N.42°E., 32 lks. dist. mkd. T29S R8W S34 BT.

A Laurel 10" dia., bears S.54°E., 24 lks. dist. mkd. T30S R8W S2 BT.

A Laurel 5" dia., bears S.38°W., 68 lks. dist. mkd. T30S R8W S3 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Feb. 9, 1970 - C.S. File 54/38-25

Found - 40" D.Fir now 47", N.42°E., 21.1 ft. Bark scribe visible "T,W,B".

10" Laurel, now down, S.54°E., 15.8 ft. This probable BT has old "X" on it, however, out of ground and down hill from where it should be.

No trace of SW. BT.

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S R8W S 34
T 30 S R8W S 3 | S 2

1970

New BTs- 6" Cedar N.4°E., 32.8 ft. scribed T29S R8W S34 CSBT
13" Cedar S.75°E., 31.7 ft. scribed T30S R8W S2 CSBT
35" D.Fir S.2°W., 11.5 ft. scribed T30S R8W CS BT S3
Corner lies approx. 230 ft. West of cor. for 34 & 35, T29-8

Fd. OK, Jan. 1980 by H. Johnstone - M 79-15

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1972, surveyed April/May 2001- (DCSO rec. Vol. 54 Page(s) 20949-50)

The cor of secs. 2 & 3 only, T30S R8W., perpetuated by the Douglas County Surveyor's Office, in 1970, monumented with an iron post, 1½" dia., firmly set, projecting 18" above ground, with brass cap mkd.

from which the remains of an original bearing tree

A sawed fir stump, 46" dia., bears N.42°E., 21.1 ft., with no marks visible.

and remains of bearing trees mkd. by the Douglas County Surveyor's Office

continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION C.C. for Secs. 2 & 3 only, North

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A cedar, 11" dia., bears N.4°E., 33.9 ft., with a healed blaze.

A cedar snag, 13" dia., 8 ft. high, bears S.75°E., 31.7 ft., with scribe marks T30S R8W S2 CS on upper and BT visible on lower partially healed blazes.

A roothole bears S.2°W., 11.5 ft., with sawed stump, 33" dia., lying alongside, with no marks visible.
and remains of a unrecorded bearing tree mkd. by person(s) unknown

A sawed cedar stump, 24" dia., bears N.9¼°E., 26.9 ft., with an X mkd. in the bark and a healed blaze.
and a new reference monument

A rebar, 36" long, 5/8" dia., driven 35" in the ground for a reference monument, bears S.65°14'09"E., 32.32 ft., with alum. cap mkd. RM T30S R8W S2 32.32 FT TO COR 2001 and an arrow pointing to the corner.