

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; and S. 2, T31-8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 17 Pages 7311-12)

Set a Fir post 3 ft. long, 3" sq., 18" in the ground for the 1/4 sec. cor. mkd. 1/4 S on the N. side and from which

A Hemlock 6" dia., bears S.11°W., 29 lks. mkd. 1/4 S BT.

A Fir 16" dia., bears N.75°W., 21 lks. mkd. 1/4 S BT.

BLM Remonumentation by White and Corbin, Cadastral Surveyor, under Group #446, Surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 31 Page(s) 13210)

The 1/4 sec. cor., determined at record distance from the original bearing trees:

A Fir 34" dia., bears N.81°W., 21 lks. dist. mkd. 1/4 on a bark blaze. (Rec. brg. N.75°W.)

A Hemlock 12" dia., bears S.19°W., 29 lks. with visible scribe marks on opened blaze. (Rec. brg. S.11°W.)

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 21" in the ground, with brass cap mkd:

T 30 S R 8 W

1/4 S 35

 S 2

T 31 S

1962

from which new bearing trees:

A Fir 34" dia., bears N.70 1/2°E., 50 lks. mkd. 1/4 S35 BT.

A Fir 40" dia., bears S.67°E., 126 lks. mkd. 1/4 S2 BT.

Fd. and used in BLM Resurvey by Charles E. Akin, Jr., Cadastral Surveyor under Group #795, Surveyed Aug/Sept. 1972 - (DCSO records Vol. 37 Page(s) 15223-24)

Fd. OK, Jan. 2002 by T. Rambo - M139-47

Fd. OK, July 2007 by T. Rambo - M153-45

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2192, Surveyed June/July 2008 - (DCSO records Vol. 56 Page(s) 22144-5)

The 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2" dia., firmly set, projecting 6" above the ground, with brass cap (properly) mkd from which the remains of the original bearing trees

A fir, 24" dia., bears S.19°W., 19.1 ft., with a healed blaze. (Record, hemlock)

A sawed, decayed fir stump, 28" dia., bears N.81°W., 13.9 ft., with no marks visible and a metal cap. CONT.

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; and S. 2, T31-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of the bearing trees mkd. by White and Corbin, reported by Akin

A sawed fir stump, 29" dia., bears N.70½°E., 33.0 ft., with scribe marks S35 BT visible on a partially healed blaze and a metal cap.

A sawed fir stump, 43" dia., bears S.67°E., 83.2 ft., with a healed blaze.

and a new bearing tree

A fir, 11" dia., bears N.59¼°W., 12.4 ft., mkd.¼ S35 BT.