

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

<p>GL0 survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7330)</p> <p>-----</p> <p>Set a laurel post, 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on N face; from which</p> <p> A laurel, 4" dia., bears S.50°W., 8 lks., mkd: ¼ S BT.</p> <p> A cedar, 8" dia., bears N.25°E., 15 lks., mkd: ¼ S BT.</p>
<p>Howard W. Johnstone - For: Roseburg Lumber Co. - Wit: R. Henrickson & J. Clark - Sept. 15, 1961 - C.S. File 51/163-5</p> <p>-----</p> <p>Found - 12" Cedar N.25°E. 9.9 ft., down, scribe visible.</p> <p>Set - 1" x 36" Iron Pipe</p> <p> 5" W. Fir S.70°W., 55.8 ft. ¼ S23 BT.</p> <p> 13" D.Fir N.80½°E., 23.0 ft. ¼ S14 BT.</p>
<p>David Edwards - Crew: Brant Miller & Eric Sprinkle - 6/26/2014 - C.S. File 65/82-55</p> <p>-----</p> <p>Found - 1" dia. iron pipe.</p> <p> A 20" dia. Fir with healed blaze bears S.70°W., 55.8 ft.</p> <p> A dead 22" dia. Fir bears N.80½°E., 23.0 ft.</p> <p>New - A 10" dia. Cedar scribed "¼ S14 BT" bears N.30°W., 33.1 ft.</p> <p> A six ft steel post is set 2 ft East</p> <p> Compass decl. 15½°E.</p>