TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Secs. 11 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7331)

Set a stone 12x12x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A laurel, 9" dia., bears N.15°E., 30 lks., mkd: ¼ S BT.
A fir, 28" dia., bears S.9°W., 38 lks., mkd: ¼ S BT.

BLM dependent resurvey by Donald R. Beck & C. Albert White, Cadastral Surveyor, under group #350 & 548, surveyed May 1963/July 1964 - (DCSO records Vol. 32 Page(s) 13601)

Point for the ¼ sec. cor. of secs. 11 & 14, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 21" in the ground with brass cap marked: T30S R8W ¼ S 11 / S 14 1964
from which
A fir, 14" dia., bears N.17°E., 45 lks., mkd: ¼ S11 BT.
A fir, 15" dia., bears S.79°W., 52 lks., mkd: ¼ S14 BT.

David Edwards - Crew: Brant Miller & Eric Sprinkle - 11/10/2017 - C.S. File 65/99-28

Found - Standard BLM Brass capped iron pipe.
A 24" dia. Fir with healed blaze bears N.17°E., 29.7 ft.
A 20" dia. Fir stump bears S.79°W., 34.3 ft.
New - An 8" dia. Fir scribed "¼ S14 BT" bears S.11°W., 6.6 ft.
Dec. 15°E.