

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 544700

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 35 only, T29-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6576-77)

Set ¼ sec. post, from which
A Fir 12" dia., bears S.35°W., 4 lks. dist.
A Laurel 15" dia., bears N.40°E., 36 lks. dist.

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 16 Page(s) 6609)

Old ¼ sec. cor. post and trees standing.

BLM resurvey by Charles E. Akin, Jr.; James E. Jelley, Cadastral Surveyors and Bruce A. Shaner, RLS #430, under Contract #52500-CT5-1117 - Surveyed June 1973/April 1976 Under Group #'s808; 858; 860, - (DCSO records Vol. 39 Page(s) 15751)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 29 S R 8 W
 ¼ S 35
T 30 S R 8 W
 1975

from which
A Fir 5" dia., bears N.80½°E., 28 lks. dist. mkd. ¼ S35 BT
A W.Fir 8" dia., bears N.72°W., 25 lks. dist. mkd. ¼ S35 BT.