

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7314)

Set a stone 15x14x4", 10" in the ground for 1/4 sec. cor. mkd. 1/4 on W side, from which

A pine, 5" dia., bears S.80°E., 36 lks., mkd: 1/4 S BT.

A laurel, 10" dia., bears S.85°W., 71 lks., mkd: 1/4 S BT.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - D. Stewart - Feb. 19, 1981 - C.S. File 61/19-6

Found - Orig. stone marked "1/4" on west side. Since bearing & dist. to remaining orig. BT did not fit well & because the dirt under the stone was covered with leaves & needles which were not even rotted, I decided the stone was not in its orig. position. The proper position of the corner bears N.8°E., 5.0 ft. from the found position of the stone.

Fd. orig. 5" now 30" Pine which had recently been cut into showing scribe marks: S visible. This tree barber chaired sometime after it was cut into, leaving a 12'-15' stump. Tree bears East 25.1 ft. from found position of stone instead of S.80°E., 23.8 ft. (Record).

Set - At record bearing and distance from orig. BT (N.80°W., 23.8 ft.) I set a 2 1/2"x30" IP with brass cap stamped: Douglas County Surveyor 1981 T30S R8W 1/4 S35 S36, 26" into the ground and place orig. stone along side.

New BTs- 20" Pine scribed 1/4 S36 CS BT in double blaze bears S.29°E., 11.5 ft.

20" Pine scribed 1/4 S35 CS BT in double blaze bears N.68°W., 7.3 ft. All three trees have DCSO BT tags.

Note - The found stone had a visible line on it showing where it had been buried in the ground years back.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2192, Surveyed June/July 2008 - (DCSO records Vol. 56 Page(s) 22147-8)

The 1/4 sec. cor. of secs. 35 & 36, perpetuated by Quibell, in 1981, monumented with an iron post, 1 1/4" dia., firmly set, projecting 3" above the ground (alongside of which is the original basalt stone, 15x14x4", lying loose, mkd. 1/4 on W. face), with brass cap (properly) mkd.

continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of an original bearing tree
A decayed pine stump, 36" dia., bears S.80°E., 23.8 ft.
with no marks visible.
and the remains of bearing trees mkd. by Quibell
A decayed pine stump, size indeterminate, bears S.29¾°E.,
11.4 ft., with no marks visible.
A decayed pine stump, size indeterminate, bears N.67¼°W.,
7.4 ft., with no marks visible.
and new bearing trees
A madrone, 13" dia., bears S.35°E., 16.9 ft., mkd.¼ S36 BT
in the bark.
A fir, 11" dia., bears N.55½° W., 18.5 ft., mkd.¼ S35 BT.
Bury original stone alongside the iron post.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)
driven at the base right side-center.