

PRIMARY CORNER DESCRIPTION Cor Secs 25, 26, 35 & 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7314)

-----

Set a fir post, 4 ft. long, 4" sq., 20" in the ground for cor. to secs. 25, 26, 35, & 36, marked T30S R8W S25 on NE, S36 on SE, S35 on SW, S26 on NW face. Also 1 notch on S & E angles of the same; from which

- A fir, 16" dia. bears N.36°E., 75 lks mkd: T30S R8W S25 BT
- A fir, 12" dia. bears S.60°E., 43 lks mkd: T30S R8W S36 BT
- A cedar, 12" dia., bears S.38°W., 10 lks., mkd: T30S R8W S35 BT.
- A laurel, 8" dia., bears N.36°W., 15 lks., mkd: T30S R8W S26 BT.

R.H. Gee - Oct. 29, 1956 - C.S. File 42/181

-----

Set 5/8" pipe for sec. corner from existing BTs which are in good condition, from which

- A fir, 24", N.36°E., 49.5 ft. old BT
- A Fir, 20" bears S.60°E., 28.4 ft. old BT, BLM tag.
- A W.Fir, 8" bears S.57°15'E., 41.5 ft scribed "S35 BT", New BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby & Jack Barnett - April/May 1965 - C.S. File 53/67-38

-----

Found - Orig. 16", now 24" Fir Snag N.36°E. 49.5 ft., dirt fill around base make it impossible to open.  
Orig. 12", now 15", snag, S.60°E. 28.4 ft., open & shows "T30S"

Set brass Cap at Cor mkd: County Surveyors T30S R8W S 26 | S 25  
Office, 1965 S 35 | S 36

New BTs- 16" W.Fir N.50°W. 20.4 ft. mkd: T30S R8W S26 CS BT  
14" W.Fir N.24°E. 46.6 ft. mkd: T30S R8W S25 CS BT  
12" W.Fir S.3°W. 51.6 ft. mkd: T30S R8W S35 CS BT  
No tree close in section 36.

Note - From our Brass Cap, R. H. Gee's I.P. bears N.49°W. 10.2 ft. & also BT 8" W.Fir bears S.60°W., 41.5 ft. from 5/8" IP not S.57¼°E.

BLM dependent resurvey by Wayne L. Rogers, Lance J. Bishop, and James L. White, Cadastral Surveyors under Group No. 1240 surveyed Feb/July 1985 - (DCSO records Vol. 47 Page(s) 18107)

-----

The cor. of sees. 25, 26, 35, & 36, perpetuated & recorded by Tracy, in 1965, monumented with an iron post, 1¼" dia., firmly set, projecting 6 ins, above ground, with brass cap (properly) mkd. continued next page

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which the remains of an original BT  
A fir snag, 14" dia., bears S.60°E., 43 lks., with scribe marks T30S visible on opened blaze.  
and bearing trees mkd. by Tracy  
A G.Fir, 17" dia., bears S.4°W., 79 lks., with healed double blaze.  
A G.Fir, 20" dia. bears N.50°W., 31 lks., with fragmentary scribe marks visible on partially healed double blaze.  
and new bearing trees  
A fir, 4" dia., bears N.18°E., 11 lks., mkd. X BT.  
A fir, 9" dia. bears S.63°E., 81 lks. mkd. T30S R8W S36 BT  
From this point, a point established by Gee, in 1956, bears N.49°W., 0.15 chs. monumented with an iron pipe, ½ in. diam., firmly set, projecting 8" above ground, from which a bearing tree mkd. by Gee:  
A G.Fir, 18" dia., bears S.60°W., 63 lks., with healed blaze.

Fd. Ok by David Edwards, 2/2005 - C.S. 65/55-1 - Set 6' post 2' west.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2192, Surveyed June/July2008 - (DCSO records Vol. 56 Page(s) 22148-9)  
-----  
The cor. of secs. 25, 26, 35, & 36, monumented with an iron post, 1¼" dia., firmly set, projecting 8" above ground, with a brass cap (properly) mkd.  
from which the remains of an original bearing tree  
A roothole bears S.60°E., 28.4 ft., alongside of which are remnants of a decayed fir stump, size indeterminate, with no marks visible.  
and the remains of BTs mkd. by Tracy, in 1965, reported by Rogers, Bishop, and White  
A decayed fir snag, 20" dia., bears S.4°W., 52.1 ft., with a healed blaze.  
A sawed fir stump, 24" dia., bears N.50°W., 20.5 ft., with no marks visible on a partially healed double blaze.  
and the remains of the BTs mkd. by Rogers, Bishop, and White  
A sawed fir stump, 12" dia., bears N.18°E., 7.3 ft., with no marks visible.  
A fir, 16" dia., bears S.63½°E., 53.5 ft., with a healed blaze.  
and a new bearing tree  
A cedar, 9" dia., bears S.37¼°W., 20.5 ft., mkd. T30S R8W S35 BT.  
continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor Secs 25, 26, 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

From this corner, a point established by Gee, in 1956, bears N.49°09'12"W., 10.24 ft., monumented with an iron pipe, ½" dia., firmly set, projecting 8" above the ground, with a hex nut on top, from which a bearing tree mkd. by Gee, reported by Rogers, Bishop, and White

A fir, 19" dia., bears S.57°W., 41.6 ft., with a healed double blaze. (Record, S.60°W.)

Corner is located 15 ft. W. of a dirt road, 12 ft. wide, bears N.35°E. and S.15°W., in curve.