

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor Secs 23, 24, 25, & 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7316)  
-----  
Set an Alder post 4 ft. long, 4" sq., 20" in the ground for the corner to Secs. 23, 24, 25, & 26, marked T30S R8W S24 on the NE face, S25 on the SE face S26 on the SW face and S23 on the NW face. Also 2 notch(es) on the S and 1 notch on the E angles of same, and from which  
A yew, 12" dia. bears N.67°E., 32 lks mkd: T30S R8W S24 BT  
A fir, 15" dia. bears S.18°E., 33 lks mkd: T30S R8W S25 BT  
A fir, 10" dia. bears S.80°W., 31 lks mkd: T30S R8W S26 BT  
An Alder, 4" dia., bears N.42°W., 18 lks., mkd: T30S R8W S23 BT.

R.H. Gee - March 1955 - C.S. File 41/385-2  
-----  
Found Yew BT which is down. Reset corner from this BT  
Set a 4" x4"x4' cedar post from which bears:  
A fir stump, 22" N.79°W., 34.0 ft. marked S23, T30S R8W WM  
A Fir stump, 20" S.73°W., 54.5 ft. marked S26, T30S R8W WM  
A Fir, 36", S.21°E., 110.0 ft. marked S25, T30S R8W WM. A metal tag was placed on this tree.  
A Fir 28", N.71°10'E., 43.7 ft. marked S24, T30S R8W WM  
The bark was removed from the stumps. Area in sections 23, 24, & 26 have been logged.

8-14-1958 - DCSO - Steel fence post has been placed at corner, C.S. File 49/108

Douglas Co. Surveyors Office - Gary Langlitz - Peter Earle - June 26, 1974 - C.S. File 56/51-26  
-----  
Found - 4"x4" scribed wood post, nearly rotted off, mkd. "S 23" on NW face; "S 24" on NE face; "S 25" on SE face and "S 26" on SW face, with steel fence post set alongside. 1955 from which:  
A 28" now 32" D.Fir bears N.71 E., 43.7 ft. scribing visible on unhealed blaze.  
A 36" now 48" D.Fir bears S.21°E., 108.8 ft. (Rec. S.21°E., 110.0 ft.) scribing visible on unhealed blaze.  
We find Yew wood remains in approx. position of orig. NE BT, no markings found.  
Logging activity has destroyed all other recorded BTs for this corner.  
Set - We remove the scribed cedar post and replace it with a Brass cap set flush with the ground mkd:  
continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>COUNTY SURVEYORS OFFICE 1974</p>	<p>T 30 S S 23   S 24 S 26   S 25 R8W</p>
<p>Reset scribed wood post and steel fence post alongside brass cap and mark the following: New BT - An 8" D.Fir bears N.44°W., 73.7 ft scribed "T30S R8W S23 CS BT" No trees near to SW. Compass declination setting 20 East.</p>	
<p>BLM dependent resurvey by Wayne L. Rogers, Lance J. Bishop, and James L. White, Cadastral Surveyors under Group No. 1240 surveyed Feb/July 1985 - (DCS0 records Vol. 47 Page(s) 18109) ----- The cor. of secs. 23, 24, 25, and 26, perpetuated by Gee, in 1955, from original evidence no longer in existence, and further perpetuated and recorded by Langlitz, in 1974, monumented with an iron post, 1¼" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd. from which the remains of bearing trees mkd. by Gee     A fir, 40" dia, bears N.71°E., 66 lks., with healed double blaze.     A fir snag, 46" dia, bears S.22½°E., 165 lks., with healed blaze. and a bearing tree mkd. by Langlitz     A fir, 15" dia, bears N.45°W., 112 lks., with healed double blaze. and new bearing trees     A fir, 13" dia, bears S.50°E., 29 lks., mkd. T30S R8W S25 BT.     A fir, 5" dia, bears S.27¾°W., 14½ lks., mkd. X BT.</p>	
<p>Ron Quimby - Crew: J. Leonard &amp; N. Fromdahl - 5/2014 - C.S. File 65/82-38 ----- Condition report Found - DCS0 brass cap     46" D.Fir N.71°E., 43.6 ft. good scar.     20" D.Fir S.50°E., 19.1 ft. good scar.     52" D.Fir S.22°E., 108.9 ft. good scar (not a snag)     10" D.Fir S.27°W., 9.6 ft. good scar.     28" D.Fir N.45°w., 73.9 ft. good scar. Note - Cor. is approx. 150' east of road I bottom area.     Compass decl. 15½°E.</p>	
<p style="text-align: right;">2</p>	