

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7318)  
-----  
Set laurel post, 3 ft. long, 3" sq., 18" in the ground, for 1/4 sec. cor., marked 1/4 S on W face; from which  
    A laurel, 10" dia., bears N.56°E., 9 lks., mkd: 1/4 S BT.  
    A fir, 10" dia., bears S.45°W., 15 lks., mkd: 1/4 S BT.

Howard W. Johnstone - For: Lumber Co. - May 28, 1962 - C.S.  
File 51/163-2  
-----  
Found - 10" Fir S.45°W. 15 lks. (scribe visible)  
Set - 1" by 24" Iron Pipe  
Scribed- 14" D.Fir N.13°W. 28.6 ft.  
          8" Chinquapin S.23°E. 30.6 ft.

Ron Quimby - Crew: J. Leonard & N. Fromdahl - 5/2014 - C.S.  
File 65/82-39  
-----  
Found - 1" I.Pipe  
          11" chincapin S.23°E., 30.6 ft. vis. scribes.  
          24" D.Fir S.45°W., 9.9 ft. good scar.  
          30" D.Fir N.13°W., 28.6 ft. good scar.  
New - A 20" D.Fir N.73°E., 16.1 ft. scribed 1/4 S24 BT.  
      Compass decl. 15 1/2°E.