

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7322)

-----  
Set a stone 26x5x5", 15" in the ground for ¼ sec. cor. mkd. ¼ on the W face, from which  
A Live Oak, 7" dia., bears S.82°E., 18 lks., mkd: ¼ S BT.  
A Live Oak, 6" dia., bears N.28°W., 16 lks., mkd: ¼ S BT.

BLM dependent resurvey by Donald R. Beck & C. Albert White, Cadastral Surveyor, under group #350 & 548, surveyed May 1963/July 1964 - (DCSO records Vol. 32 Page(s) 13596-7)

-----  
The ¼ sec. cor. of secs. 11 and 12, determined at record distance from the original bearing trees:

A live oak, 10" dia., bears S.80½°E., 18 lks. with visible scribe marks on opened blaze. (Record bearing, S.82°E.)  
A live oak, 8" dia., bears N.41°W., 16 lks., with scribe mks. ¼ S on opened blaze. (Record bearing, N.28°W.)

At the corner point

Set an iron post, 28" long, 2½" dia., 12" in the ground, to solid rock, & supported in a mound of stone, 3 ft. base, to top, with brass cap marked:

T30S R8W  
¼  
S 11|S 12  
1964

from which new BTs

A fir, 20" dia., bears N.38¼°E., 80 lks., mkd: ¼ S12 BT.  
A fir, 10" dia., bears S.73½°W., 36½ lks., mkd: ¼ S11 BT.