

PRIMARY CORNER DESCRIPTION Cor Secs 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7322)

Set a chincapin post 4 ft. long, 4" sq., 20" in the ground for the corner to Secs. 1, 2, 11, & 12, marked T30S R8W S1 on the NE face, S12 on the SE face S11 on the SW face and S2 on the NW face. Also 5 notches on the South and 1 notch on the East angles of same, and from which

- A laurel, 14" dia., bears N.24°E., 23 lks., mkd: T30S R8W S1 BT.
- A fir, 18" dia., bears S.17°E., 41 lks., mkd: T30S R8W S12 BT.
- A laurel, 12" dia., bears S.64°W., 31 lks., mkd: T30S R8W S11 BT.
- A chincapin, 8" dia., bears N.68°W., 39 lks., mkd: T30S R8W S2 BT.

BLM dependent resurvey by Donald R. Beck & C. Albert White, Cadastral Surveyor, under group #350 & 548, surveyed May 1963/July 1964 - (DCSO records Vol. 32 Page(s) 13597-8)

The cor. of secs. 1, 2, 11, & 12, determined at record bearing & distance from the remains of the original BTs:

- A madrone, 23" dia., bears N.24°E., 23 lks., with no mks. visible.
 - A sawed fir stump, 36" dia., bears S.17°E., 41 lks., with a healed blaze.
 - A madrone snag, 10" dia., bears S.64°W., 31 lks., with visible scribe mks. on open blaze.
 - A down chinquapin, 12" dia., bears N.68°W., 39 lks., with old axe inks, visible on open blaze.
- and local bearing trees
- A fir, 7" dia., bears S.81°E., 50 lks., mkd. S12 T30S R8W BT on double blaze.
 - A hemlock, 19" dia., bears S.44¼°W., 57 lks., with a partially healed double blaze.
 - A hemlock, 18" dia., bears N.84°W., 51 lks., mkd. S2 T30S R8W BT on double blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T30S	R8W
S 2 S 1	
S 11 S 12	
1964	

from which a new BT

- A fir, 10" dia. bears N.40¼°E., 65 lks mkd: T30S R8W S1 BT

FD. GLO BC & BTs by DCSO J. Powell, 5/4/1970 C.S. 53/67-9