

PRIMARY CORNER DESCRIPTION 1/4 cor. Secs. 25 & 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7315)

Set a stone 14x14x8", 10" in the ground for 1/4 sec. cor. mkd. 1/4 on N face, from which
 A fir, 8" dia., bears S.33°W., 80 lks., mkd: 1/4 S BT.
 A live oak, 4" dia., bears N.59°W., 33 lks., mkd: 1/4 S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby & Jack Barnett - April/May 1965 - C.S. File 53/67-43

Found - Rock Mkd: "1/4" on N. face, 14"xl3"x8", as called for. Orig. 8", now 37" Fir S.33°W., 52.8 ft. Open & shows good "S" scribe. No trace of other BT.
Set brass cap at Cor. Mkd: County Surveyors T30S R8W 1/4 S 25
 Set Rock alongside Office, 1965 S 36
New BTs- 9" D.Fir S.8°W. 8.7 ft. mkd. 1/4 S36 CS BT.
 8" D.Fir N.30°W. 9.0 ft. mkd. 1/4 S25 CS BT.
Note - This corner lies approx. 25.0 ft. East of top of small spur, ridge sloping S.20°E.

BLM dependent resurvey by Wayne L. Rogers, Lance J. Bishop, and James L. White, Cadastral Surveyors under Group No. 1240 surveyed Feb/July 1985 - (DCSO records Vol. 47 Page(s) 18106)

The 1/4 sec. cor. of secs. 25 and 36, perpetuated and recorded by Tracy, in 1965, monumented with an iron post, 1 1/4" dia., firmly set, projecting 6" above ground, with original stone alongside, firmly set, projecting 4" above ground, with marks 1/4 visible on N. face, with brass cap (properly) mkd. from which the remains of an original BT
 A sawed fir stump, 31" dia, bears S.33°W., 80 lks., with fragmentary scribe marks visible on opened blaze.
and the remains of bearing trees mkd. by Tracy
 A sawed fir stump, 14" dia, bears S.7°W., 13 lks., with healed double blaze.
 A fir, 14" dia, bears N.34°W., 14 lks., with healed double blaze.
and a new bearing tree
 A fir, 10" dia, bears S.46°E., 34 lks., mkd. 1/4 S36 BT.

Bruce Shaner - For: Seneca Jones Timber Co - 4/2002 - M139-72 - C.S. File 65/42-42A

Found - 1" IP with 2 1/2" BC, properly marked, from which a:
 32" D.Fir, now 6 ft. high stump, opened face, bears S.33°W., 52.8 ft.
continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 cor. Secs. 25 & 36

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

	14" D.Fir, now 6 ft. high stump, opened face, bears S.7°W., 8.6 ft.
	18" D.Fir, face overgrown, bears N.34°W., 9.2 ft.
	14" D.Fir, face overgrown, bears S.46°E., 22.4 ft.
New -	6 ft. steel fence post, West, 1.0 ft.