

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 640240

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 25

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM dependent resurvey by Wayne L. Rogers, Lance J. Bishop,  
and James L. White, Cadastral Surveyors under Group No. 1240  
surveyed Feb/July 1985 - (DCSO records Vol. 47 Page(s) 18113)

-----  
Point for the center ¼ sec. cor. of sec. 25, at intersection  
with the E. and W. center line.

Set a stainless steel post, 28", long, 2½" dia., 24" in the  
ground, with brass cap mkd. T30S R8W

C ¼  
S 25  
1985

from which

A fir, 4" dia., bears N.60½°E., 26 lks., mkd. X BT.

A fir, 5" dia., bears S.39°E., 12 lks., mkd. C¼ S25 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless  
steel post.

-----  
David Edwards - For: Seneca Jones Tmbr Co. - April 2017 -  
C.S. File 65/96-6

Found - 1985 BLM brass capped iron pipe.

An 8" dia., Fir bears N.60½°E., 17.2'

A 10" dia., Fir bears S.39°E., 7.9'

Both with healed blazes.

A 6 ft. steel post is set 2 ft. north on line.