

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias	Description

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 17 Page(s) 7319)

Set a cedar post 3 ft. long, 3" sq., 18" in the ground, for 1/4 sec. cor., marked 1/4 S on N side and from which
 A cedar, 14" dia., bears N.68°E., 20 lks., mkd: 1/4 S BT.
 A fir, 15" dia., bears S.24°E., 13 lks., mkd: 1/4 S BT.

Reported as not found by DCSO VRT 4/1/1965 C.S. File 53/67-50

Greg Lang - For: Roseburg Resources - 3/2006 - M150-3 & C.S. File 65/58-2B

Found - A thorough search was made for the orig. corner. It was not found.
Set - 5/8" x 36" iron rod with 2 1/2" aluminum cap marked as shown above. Corner was set by proportionate Measurement according to the distances given in the original 1882 survey.
 A 20" Fir bears S.74°E., 13.70 ft scribed "1/4 S24 BT"
 A 14 1/2" W.Fir bears S.48 1/2°W., 25.90 ft scribed "1/4 S24 BT"
 A 12" W.Fir bears N.54 1/2°W., 15.20 ft scribed "1/4 S13 BT"
 A 14" W.Fir bears N.31 1/2°E., 6.40 ft scribed "1/4 S13 BT"
Note - We set spikes in the base of all new BTs for measuring distances to the corner; bearings to the trees were measured with a total station & are based on the 1882 GLO Survey by Byars.
 Corner lies on a gentle westerly slope & about 450' easterly of a gravel road.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor under Group No. 2139, surveyed July/Aug. 2006 (DCSO records Vol. 57 Page(s) 22539)

The 1/4 sec. cor. of secs. 13 & 24, reestablished by Lang, in 2006, and is accepted as the cor., monumented with an iron rebar, 5/8" dia., firmly set, projecting 4" above ground, with aluminum cap (properly) mkd.
from which bearing trees mkd. by Lang
 A fir, 14" dia., bears N.32°E., 6.4 ft., with scribe marks 1/4 S13 BT visible on an open blaze.
 A fir, 20" dia., bears S.73°E., 13.7 ft., with scribe marks 1/4 S24 BT visible on an open blaze.
 A fir, 15" dia., bears S.48 1/2°W., 25.9 ft., with scribe marks 1/4 S24 BT visible on an open blaze. cont.

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

A fir, 12" dia., bears N.54°W., 15.2 ft., with scribe marks ¼ S13 BT visible on an open blaze.