

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 25; & 30, T30-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7250)

Set a Fir post 3 ft. long, 3" sq., 18" in the ground for the 1/4 sec. cor. marked 1/4 S. on the W. side, from which
A Fir 10" dia., bears S.72°E., 22 lks. dist. mkd. 1/4 S BT.
A Fir 18" dia., bears N.64°W., 22 lks. dist. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman, crew - Feb. 1964 - C.S. File 53/40-37

Found - Orig. 10" now 18" Fir snag, S.72°E., 14.5 ft., open and find good scribing "B".
Orig. 18" now 26" R.Fir N.64°W., 14.5 ft., shows good scars.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 7 W
1/4 R8W S25|S30 R7W
1964

New - Rescribe 26" R.Fir N.64°W., 15.5 ft., bark scribe "CS"
14" R.Fir bears S.72°E. 40.6 ft scribed "1/4 S30 CS BT"

BLM resurvey by Stephen D. Albright and Jack W. Bowder, Cadastral Surveyors, under Group #787, surveyed July/Aug. 1972 - (DCSO records Vol. 35 Page(s) 14883-84)

(Corner report only)
At the 1/4 sec. cor., perpetuated and recorded by Byron in 1964, monumented with an iron post, 2" dia., firmly set, projecting 15" above ground with brass cap, from which the remains of the original bearing trees:
A Fir snag 18" dia., bears S.72°E., 22 lks. dist. with scribe mark B visible on opened blaze.
A Fir 32" dia., bears N.64°W., 22 lks. dist. with healed blaze. This tree remarked CS on bark blaze by Byron.
and trees mkd. by Byron in 1964
A Fir 16" dia., bears S.72°E., 61 lks. dist., no marks visible on pitched over blaze.

BLM dependent resurvey by Wayne L. Rogers, Lance J. Bishop, and James L. White, Cadastral Surveyors under Group No. 1240 surveyed Feb/July 1985 - (DCSO records Vol. 47 Pages 18113-4)

The 1/4 sec. cor. of secs. 25 & 30, on the E bdy of the Tp., perpetuated & recorded by Byron, in 1964, monumented with an iron post, 1 1/4" dia. firmly set, projecting 10" above ground, with brass cap (properly) mkd.

continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 25; & 30, T30-7

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

from which the remains of the original bearing trees
A fir snag, size indeterminate, bears S.72°E., 22 lks., no marks visible.
A fir, 36" dia., bears N.64°W., 22 lks., with healed blaze, rescribed by Byron, with scribe marks CS visible on bark blaze.
and the remains of a bearing tree mkd. by Byron
A sawed fir stump, 18" dia., bears S.72°E., 61 lks., with healed blaze.
and a new bearing tree
A fir, 32" dia., bears N.74°E., 98 lks., mkd. ¼ S30 BT.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2192, Surveyed June/July2008 - (DCSO records Vol. 56 Page(s) 22145-6)

The ¼ sec. cor. of secs. 25 & 30, on the E. bdy. of the Tp., monumented with an iron post, 1¼" dia. firmly set, projecting 13" above the ground, with brass cap (properly) mkd from which the remains of the original bearing trees
A broken, decayed fir stump, size indeterminate, bears S.72°E., 14.5 ft., alongside of which is a down, decayed fir snag, size indeterminate, with no marks visible.
A fir, 37" dia., bears N.64°W., 14.5 ft., with a healed blaze.
and the remains of a BT mkd. by Byron, in 1964, reported by Rogers, Bishop, and White
A decayed fir stump, size indeterminate, bears S.72°E., 40.3 ft., with no marks visible.
and the remains of a BT mkd. by Rogers, Bishop, and White
A sawed fir stump, 34" dia., bears N.74°E., 64.7 ft., with scribe marks S30 BT visible on a partially healed blaze
and a new bearing tree
A fir, 6" dia., bears S.30¼°E., 9.8 ft., mkd. ¼ S30 BT.
Corner is located 70 ft. N. of a gravel road, 12 ft. wide, bears N.70°W. and S.75°E., in curve.
For the ¼ section corner of sections 25 and 30, on the east boundary of the township:
Latitude: 42°56'03.75"N Longitude: 123°35'04.27"W.
New bearing trees have a 2½"x ¼" magnetic nail (Mag Nail) driven at the base on the center of the right side.