

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec Cor for 24 & 25; & 19 & 30, T30-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Pages 7250-51)

-----  
Marked a Fir tree 16" dia. for the cor. to secs. 19, 24, 25 and 30. Marked T30S R7W S19 on the NE.; S30 on the SE. face.; R8W S25 on the SW. face.; and S24 on the NW. face. Also two notches on the S. and four on the N. edges, and from which  
A Fir 4" dia., bears N.48°E., 13 lks mkd. T30S R7W S19 BT.  
A Fir 6" dia., bears S.58°E., 40 lks mkd. T30S R7W S30 BT.  
A Fir 24" dia., bears S.80°W., 37 lks mkd. T30S R8W S25 BT  
A Fir 7" dia., bears N.20°W., 19 lks mkd. T30S R8W S24 BT.

Not fd by DCSO 6/1965 C.S. File 53/40-76

BLM resurvey by Stephen D. Albright and Jack W. Bowder, Cadastral Surveyors, under Group #787, surveyed July/Aug. 1972 - (DCSO records Vol. 35 Page(s) 14884)

-----  
Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T	30	S
R	8	W
R	7	W
S	24	S 19
S	25	S 30
1972		

from which

A Hemlock 13" dia., bears N.10½°E., 22 lks. mkd. T30S R7W S19 BT.  
A Cedar 5" dia., bears S.68°E., 54½ lks. mkd. X BT  
A Fir 9" dia., bears S.61°W., 34 lks mkd. T30S R8W S25 BT.  
A Fir 18" dia., bears N.41°W., 31 lks mkd. T30S R8W S24 BT

Ron Quimby - Crew: J. Leonard and N. Fromdahl - 4/2014 - C.S. File 65/82-35

-----  
Found - BLM brass cap  
24" hemlock N.10°E., 14.5 ft. good scar.  
10" cedar S.68°E., 36.0 ft. good scar.  
26" fir N.41°W., 20.5 ft. good scar.  
New - A 20" fir S.76°W., 24.3 ft. scribed T30S R8W S25 BT.  
Note - Corner is 50' ± south of road to landing in SE cor. of old logging.  
Compass decl. 15½°E.

continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec Cor for 24 & 25; & 19 & 30, T30-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and  
Jeff Lorsung - 1/22/2025 - C.S. File 67/59-48

-----  
Found - BLM brass cap (properly mkd) Proj 6" galvanized post  
N.E. edge.

25" W. fir (rec hemlock) N.10°E. 14.5' good scar.

10" cedar S.68°E. 36.0' good scar.

26" fir N.41°W. 20.5' good scar.

20"x12'fir snag S.76°W. 24.3' visible scribes

Add new tags to all trees

OCRS COORDINATE SYSTEM

COTTAGE GROVE-CANYONVILLE ZONE

N 39508.285 E 96763.820

Note - Cor is 50'+-south of road to landing in S.E.  
corner of old logging.

Comp. decl. 14½°E.