

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24; 18 & 19, T30-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7251)

Set a stone 18 x 12 x 10 ins. for the cor. to secs. 13, 18, 19 and 24. Marked 3 notches on the S. edges and 3 notches on the N. edges from which

A Fir 12" dia., bears N.38°E., 52 lks. dist. mkd. T30S R7W S18 BT.

A Laurel 10" dia., bears S.56°E., 74 lks. dist. mkd. T30S R7W S19 BT.

A Cedar 10" dia., bears S.48°W., 29 lks. dist. mkd. T30S R8W S24 BT.

A Fir 10" dia., bears N.72°W., 15 lks. dist. mkd. T30S R8W S13 BT.

Survey by Howard W. Johnstone - For: Roseburg Lumber Co. - Sept. 15, 1961 - C.S. File 51/163-5

Could not locate the original corner stone.

Found - 8" Fir N.72°W., 9.9 ft.

17" Fir N.38°E., 34.3 ft.

Set 1" x 30" Iron pipe in stone mound, from which

12" Fir S.69½°E., 53.0 ft.

15" Fir S.37°W., 68.5 ft.

BLM resurvey by Stephen D. Albright and Jack W. Bowder, Cadastral Surveyors, under Group #787, surveyed July/Aug. 1972 - (DCSO records Vol. 35 Page(s) 14885-86)

The Sec. cor., perpetuated and recorded by Johnstone in 1961, monumented with an iron pipe 1¼" dia., firmly set, protruding 18" above the ground, alongside of which is the original basalt stone 18 x 12 x 10 ins., firmly set, 8" in the ground, mkd. with 3 notches on the N. edge and 3 notches on S. edge. from which the remains of the original bearing trees:

A Fir 18" dia., bears N.38°E., 52 lks. dist. with illegible scribe marks visible on opened blaze.

A rotted Madrone stump, size indeterminate, bears S.56°E., 74 lks. dist., no marks visible.

A Fir 11" dia., bears N.72°W., 15 lks. dist., with healed blaze.

and trees mkd. by Johnstone in 1961:

A Fir 14" dia., bears S.69°E., 77 lks. dist. with scribe marks T30S R7W BT visible on open blaze.

A Fir 15" dia., bears S.37½°W., 102 lks. dist., with healed blaze.

(Cont. Next Page)

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24; 18 & 19, T30-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set an iron post, 28" long, 2½" dia., 10" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 30 S
R 8 W R 7 W
S 13 | S 18
S 24 | S 19
1972

Reset iron pipe and deposit corner stone alongside the iron post.

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1350, Surveyed April/May 1987 - (DCSO records Vol. 48 Page(s) 18386-87)

The sec. cor., monumented with an iron post, 2½" dia., firmly set, projecting 18" above ground, in a mound of stone, 4 ft. base, to top, (with original basalt stone, 18x12x10 ins. mkd. with 3 grooves on the S. face and 3 grooves on the N. face, and an iron post 1½" dia., alongside) with a 1972 brass cap from which the original bearing trees:

A Fir 20" dia., bears N.38°E., 53 lks. dist. with healed blaze. (Rec. 52 lks.)

A Fir 12" dia., bears N.72°W., 15 lks. dist. with healed blaze.

and the remains of the bearing trees mkd. by Johnstone in 1961:

A sawed Fir stump, 15" dia., bears S.69°E., 77 lks. dist., with scribe marks N B visible on a partially healed blaze.

A Fir 19" dia., bears S.37½°W., 102 lks. dist. with healed blaze.

and a new bearing tree:

A Madrone 8" dia., bears S.61°E., 68½ lks. dist. mkd. T30S R7W S19 BT.

Fd. 0k by Greg Lang, 3/2006 - M150-3

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor under Group No. 2139, surveyed July/Aug. 2006 (DCSO records Vol. 57 Page(s) 22536-7)

The cor. of secs. 13, 18, 19, & 24, on the E. bdy. of the Tp., monumented with an iron post, 2½" dia., firmly set, projecting 16" above ground (with an iron pipe, 1½" dia., projecting 20" above ground alongside), in a mound of stone, 3 ft. dia., 12" high, with brass cap (properly) mkd. from which the remaining original bearing trees

continued next page

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24; 18 & 19, T30-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 24" dia., bears N.38°E., 35.0 ft., with a healed blaze.
A fir, 17" dia., bears N.72°W., 9.9 ft., with a healed blaze.
and remains of BTs mkd. by Johnstone, in 1961
A sawed fir stump, 15" dia., bears S.69°E., 50.8 ft., with scribe marks BT visible on a partially healed blaze.
A fir, 24" dia., bears S.37½°W., 67.3 ft., with a healed blaze.
and bearing tree mkd. by Bedell
A madrone, 11" dia., bears S.59¼°E., 45.2 ft., with a healed blaze. (Record, S.61°E.)
From this cor., an unrecorded iron rebar, 5/8" dia., firmly set by person(s) unknown, projecting 3" above ground, bears S.61°58'00"W., 3.03 ft., with no cap.

Ron Quimby - Crew: J. Leonard & N. Fromdahl - 4/2014 - C.S.
File 65/82-37

Condition report
Found - 2½" I.P. with brass cap.
28" fir N.38°E., 35.0 good scar.
16" fir stump S.69°E., 50.8 vis. scribe
14" madrone S.59°E., 45.2 ft. good scar.
26" fir S.37°W., 67.3 ft. good scar.
5/8" rebar S.62°W., 3'
20" fir N.72°W., 9.9 ft. good scar.
Compass decl. 15½°E.