

TOWNSHIP 30 RANGE 08 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 12; & 7 of T30-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 450 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7253)

Set a Laurel post 3 ft. long, 3" sq. 18" in the ground for the ¼ sec. cor. marked ¼ S on the W. side, from which

A Laurel 20" dia., bears N.29°E., 11 lks. dist. mkd. ¼ S BT.

A Laurel 8" dia., bears S.75°W., 29 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman, crew - Feb. 1964 - C.S. File 53/40-47

Found - Orig. 8" now 12" Laurel N.75°W., not S.75°W., 19.1 ft. We open and find good scribing.

Orig. 20" now 30" Laurel N.29°E., 7.3 ft., center rotted, no scribing.

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S
R8W ¼ S12 | S7 R7W
1964

New BTs -7" R.Fir bears N.58°W., 17.3 ft. scribed ¼ S12 CSBT

12" R.Fir bears S.16°E., 15.2 ft. scribed ¼ S7 CSBT

Fd. BC & 3 BTs by D. Edwards, 1/2009 - M158-50