

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 30; & 25, T30-10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7379)

Marked a Fir 18" dia., for ¼ sec. post, from which
A Laurel 15" dia., bears N.4°W., 59 lks. dist.
A Fir 15" dia., bears N.52°E., 28 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #613, dated April 29, 1893 (DCSO records Vol. 17 Page(s) 7405-06)

(35.80 chs.)
I set temp. stake, I find a Fir tree 18" dia., mkd. ¼ S on W. side, for ¼ sec. cor. on the blazed line, from which
A Fir 15" dia., bears N.52°E., 28 lks. dist. mkd. ¼ S BT
A laurel 15" dia., lying upon the ground mkd. ¼ S BT, the stump of which bears N.4°W., 59 ks. dist. mkd. ¼ S BT.
From temp. stake, the ¼ sec. cor. bears W. 3 lks. dist. I destroy the marks on the ¼ sec. tree cor. and also the marks on the bearing trees. From the temp stake:
(run North to 40.0 chs.)
I set the ¼ sec. cor. 3 lks. W. of my line to the blazed line which cor. is a stone, 15x10x5 ins., 10" in the ground for ¼ sec. cor., mkd. ¼ on W. face, from which
A Fir 48" dia., bears N.50½°W., 46 lks. dist. mkd. ¼ S BT.
A Cedar 11" dia., bears N.54°W., 61½ lks. dist. mkd. ¼ S BT.

Survey by Mark Smalley - For: Roseburg Forest Products - Feb. 1994 - M 119-18

Found - Orig. stone, broken, marked "¼".
48" Fir N.50½°W., 30.4 ft., snag. Orig. BT.
Scribed- 17" Fir N.88°W., 16.6 ft. "¼ S25 BT"
17" Fir N.2°E., 8.1 ft. "¼ S30 BT"
11" Fir S.20°E., 22.3 ft. "¼ S30 BT"
14" Fir S.19°W., 18.9 ft. "¼ S25 BT"